VERSION 2

NOV 07, 2017

Assign taxonomy to gene calls using Centrifuge V.2

James E Thornton Jr¹

¹Hurwitz Lab

Metafunc Course 2017

James E Thornton Jr

Hurwitz Lab

ABSTRACT

Uses a custom Centrifuge pipeline to assign taxonomy to gene calls.

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.kptcvnn

Protocol Citation: James E Thornton Jr 2017. Assign taxonomy to gene calls using Centrifuge. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.kptcvnn>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: Nov 07, 2017

Last Modified: Mar 01, 2018

PROTOCOL integer ID:
8659

- 1 Navigate to the directory on your local machine that contains the contigs.db generated during the [Anvi'o protocol](#).

2 Extract gene calls from the contigs database.

Command

```
$ anvi-get-dna-sequences-for-gene-calls -c CONTIGS.db -o nucleotides.faa
```

Note

Important: nucleotides.fna was generated in the prodigal protocol. HOWEVER, we will be using this version from Anvi'o for taxonomy assignment.

3 Log into the HPC

Command

```
$ ssh hpc  
$ ocelote
```

4 Move into your class directory.

Command

```
$ cd /rsgprps/bh_class/username
```

5 Make an anvio-genes directory.

Command

```
$ mkdir anvio-genes
```

- 6 On your local machine, scp the nucleotides.fna file generated from step 2 into the newly created anvio-genes directory.

Command

```
$ scp nucleotides.fna username@sftp.hpc.arizona.edu:/rsgrps/bh_class/username/anvio-genes
```

- 7 Clone the Centrifuge github repository into your class directory on the HPC.

Command

```
$ pwd
/rsgrps/bh_class/username
$ git clone git@github.com:jetjr/Centrifuge.git
```

- 8 Move into the Centrifuge directory.

Command

```
$ cd Centrifuge
```

Dependencies

- 9 This program uses R packages that must be installed prior to launching the job. Load the R module.

Command

```
$ module load unsupported
$ module load markb/R/3.1.1
```

10 Launch R.

Command

```
$ R
```

11 Get the "optparse" package.

12 Get ggplot2 and plyr packages. You may be prompted to select a mirror. Any US server will work.

Command

```
> install.packages(
```

Note

If you receive an error when installing the dependencies, continue with the protocol.

13 Quit the R session. Do not save workspace image.

Command

```
> q()  
> Save workspace image? [y/n/c]: n
```

14 Edit the config.sh file to include the correct variable declarations. The following steps will detail how the config.sh file should be edited.

Command

```
$ nano config.sh
```

CENT_DB

15 `export CENT_DB="/rsgtps/bh_class/b_compressed+h+v/b_compressed+h+v"`

FASTA_DIR

16 `export FASTA_DIR='/rsgtps/bh_class/username/anvio-genes'`

Note

FASTA_DIR should point to the directory containing your nucleotides.fna file generated from step 2 and transferred to the anvio-genes directory.

TYPE

17 `export TYPE="single"`

FILE_EXT

18 `export FILE_EXT="fna"`

REPORT_DIR

19 `export REPORT_DIR='/rsgrps/bh_class/username/anvio-genes/taxonomy/'`

Note

The program will create this directory for you. Make sure to replace username.

PLOT_OUT

20 `export PLOT_OUT='/rsgrps/bh_class/username/anvio-genes/taxonomy/'`

Note

Same as REPORT_DIR but make sure to include the trailing / as stated in the config.sh file.

PLOT_FILE and PLOT_TITLE

21 These should be named according to what sample your working with. For example, ocean data may name these:

```
export PLOT_FILE='ocean_depth'
export PLOT_TITLE='ocean_depth'
```

Note

PLOT FILE will be the file name of the bubble plot that is generated.

PLOT TITLE will be the title found on the actual plot.

FILE_TYPE

22 `export FILE_TYPE="f"`

Note

The nucleotides.fna file is in FASTA format.

EXCLUDE

23 The exclude parameter can be left blank.

```
export EXCLUDE=""
```

24 Save and quit config.sh

25 Submit the job using the submit script found in the Centrifuge directory.

Command

```
$ ./submit.sh
```

26 Status of the job can be determined by the following command:

Command

```
$ stat -u username
```

27 A successful job will generate a centrifuge_report.tsv file in anvio-genes/taxonomy.