VERSION 3

NOV 09, 2017

Assign taxonomy to gene calls using Centrifuge V.3

James E Thornton Jr¹

¹Hurwitz Lab

Metafunc Course 2017

James E Thornton Jr

Hurwitz Lab

ABSTRACT

Uses a custom Centrifuge pipeline to assign taxonomy to gene calls.

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.kq3cvyn

Protocol Citation: James E Thornton Jr 2017. Assign taxonomy to gene calls using Centrifuge. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.kq3cvyn>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: Nov 09, 2017

Last Modified: Mar 01, 2018

PROTOCOL integer ID:
8699

- 1 Navigate to the directory on your local machine that contains the contigs.db generated during the [Anvi'o protocol](#).

2 Extract gene calls from the contigs database.

Command

```
$ anvi-get-dna-sequences-for-gene-calls -c CONTIGS.db -o nucleotides.faa
```

Note

Important: nucleotides.fna was generated in the prodigal protocol. HOWEVER, we will be using this version from Anvi'o for taxonomy assignment.

Note

Remember windows users you must launch Anvio using docker.
docker run --rm -v /path/to/files:/my_data -p 8080:8080 -it meren/anvio:latest

3 Log into the HPC

Command

```
$ ssh hpc  
$ ocelote
```

4 Move into your class directory.

Command

```
$ cd /rsgrps/bh_class/username
```

5 Make an anvio-genes directory.

Command

```
$ mkdir anvio-genes
```

- 6 On your local machine, scp the nucleotides.fna file generated from step 2 into the newly created anvio-genes directory.

Command

```
$ scp nucleotides.fna username@sftp.hpc.arizona.edu:/rsgtps/bh_class/username/anvio-genes
```

- 7 Clone the Centrifuge github repository into your class directory on the HPC.

Command

```
$ pwd  
/rsgtps/bh_class/username  
$ git clone git@github.com:jetjr/Centrifuge.git
```

- 8 Move into the Centrifuge directory.

Command

```
$ cd Centrifuge
```

Dependencies

- 9 This program uses R packages that must be installed prior to launching the job. Load the R module.

Command

```
$ module load unsupported  
$ module load markb/R/3.1.1
```

10 Launch R.

Command

```
$ R
```

11 Get the "optparse" package.

Command

```
> </ProtocolCommand>  
<ProtocolNote id=
```

12 Get ggplot2 and plyr packages. You may be prompted to select a mirror. Any US server will work.

Command

```
> install.packages(
```

Note

If you receive an error when installing the dependencies, continue with the protocol.

13 Quit the R session. Do not save workspace image.

Command

```
> q()  
> Save workspace image? [y/n/c]: n
```

- 14** Edit the config.sh file to include the correct variable declarations. The following steps will detail how the config.sh file should be edited.

Command

```
$ nano config.sh
```

CENT_DB

- 15** `export CENT_DB="/rsgroups/bh_class/b_compressed+h+v/b_compressed+h+v"`

FASTA_DIR

- 16** `export FASTA_DIR="/rsgroups/bh_class/username/anvio-genes"`

Note

FASTA_DIR should point to the directory containing your nucleotides.fna file generated from step 2 and transferred to the anvio-genes directory.

TYPE

- 17** `export TYPE="single"`

FILE_EXT

18 `export FILE_EXT="fna"`

REPORT_DIR

19 `export REPORT_DIR='/rsgrps/bh_class/username/anvio-genes/taxonomy/'`

Note

The program will create this directory for you. Make sure to replace username.

PLOT_OUT

20 `export PLOT_OUT='/rsgrps/bh_class/username/anvio-genes/taxonomy/'`

Note

Same as REPORT_DIR but make sure to include the trailing / as stated in the config.sh file.

PLOT_FILE and PLOT_TITLE

21 These should be named according to what sample your working with. For example, ocean data may name these:

```
export PLOT_FILE='ocean_depth'  
export PLOT_TITLE='ocean_depth'
```

Note

PLOT FILE will be the file name of the bubble plot that is generated.

PLOT TITLE will be the title found on the actual plot.

FILE_TYPE

22 `export FILE_TYPE="f"`

Note

The nucleotides.fna file is in FASTA format.

EXCLUDE

23 The exclude parameter can be left blank.

```
export EXCLUDE=""
```

24 Save and quit config.sh

25 Move into the script directory.

Command

```
$ cd scripts
```

26 Edit the PBS variables in centrifuge_single_tax.sh to include the bh_class group and your email.

```
#PBS -W group_list=bh_class
#PBS -M netid@email.arizona.edu
```

Command

```
$ nano centrifuge_single_tax.sh
```

27 Save and quite centrifuge_single_tax.sh. Then move back into the main Centrifuge directory.

Command

```
$ cd ..
```

- 28** Submit the job using the submit script found in the Centrifuge directory.

Command

```
$ ./submit.sh
```

- 29** Status of the job can be determined by the following command:

Command

```
$ stat -u username
```

- 30** A successful job will generate a centrifuge_report.tsv file in anvio-genes/taxonomy.