VERSION 2

OCT 31, 2018

OPEN ACCESS

DOI:
[dx.doi.org/10.17504/protocols.io.u32eyqe](https://doi.org/10.17504/protocols.io.u32eyqe)

External link:
<https://doi.org/10.1371/journal.pone.0207606>

Protocol Citation: Fernando Espinola 2018. Bioinformatic analysis of biomarker genes using metagenomic shotgun sequence datasets.
protocols.io
<https://dx.doi.org/10.17504/protocols.io.u32eyqe>

MANUSCRIPT CITATION:
 Calderoli PA, Espínola FJ, Dionisi HM, Gil MN, Jansson JK, Lozada M (2018) Predominance and high diversity of genes associated to denitrification in metagenomes of subantarctic coastal sediments exposed to urban pollution. PLoS ONE 13(11): e0207606. doi: [10.1371/journal.pone.0207606](https://doi.org/10.1371/journal.pone.0207606)

Bioinformatic analysis of biomarker genes using metagenomic shotgun sequence datasets V.2

Forked from a private protocol

PLOS One

Fernando Espinola¹

¹CESIMAR-CENPAT-CONICET

Fernando Espinola

ABSTRACT

This protocol describes the steps used to analyze shotgun sequences deposited in Integrated Microbial Genomes and Microbiomes ([IMG/M](#)) by using functional annotation evidences. [KEGG orthology terms and pathways](#) are used as evidence. The abundance of each of the corresponding biomarker genes is estimated by calculating the proportion of amino acid sequences assigned to the KO of interest (estimated gene copies, assembled and unassembled metagenomes, as retrieved from IMG/M) and normalized with respect to the total number of sequences assigned to KOs in each metagenome.

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: Oct 27, 2018

Last Modified: Oct 31, 2018

PROTOCOL integer ID:
17242

Find metagenomes in the database

1

Dataset

Integrated Microbial Genomes and Microbiomes

NAME

<https://img.jgi.doe.gov>

LINK

Note

To select metagenome(s) of interest, click on the following:

Find Genomes -> Genome Search -> Quick Search with "Search Parameters: Search by ID ", and paste ID(s) in the corresponding box, separated by commas.

In our case, we searched by IDs: 3300000122, 3300000242, 3300000118, 3300000121, 3300000131, 3300000125

Note

Select the boxes on the retrieved genomes, and click "Add selected to Genome Cart"
With the genomes added to the genome cart it is possible to export them listed in an excel file.

Once the genomes have been selected and added to the genome cart all the tools present in the IMG website are available for different analyses.

In all cases be sure that the analyses were performed on your dataset. For that, check in the superior bar below the JGI/IMG icon where your data is depicted as "My Analysis Carts". It is important that the genomes number is in agreement with the genomes that have been selected.

Get the KO table from the database

- 2 Build a normalized table: divide each KO abundance in each metagenome by the number of sequences assigned to KOs
As the exported table from the IMG displays the KO terms in rows and samples columns in order to normalize the sequence abundance the total sequence count per sample should be obtained. For that, a sum function for total sum per column would be useful to get the sum of every KO term count in every sample.
For normalization, each KO term count will be divided by the total sequence count per sample. This procedure has to be applied for every sample in all dataset.

Normalize the KO table

3

Note

To obtain the KO table from the database:

Go to the menu and select the Compare Genomes item and then Abundance Profiles. Finally click on Overview (all functions) item where you will determinate several features of the KO table settings different options.

Toggle the option Matrix and then for normalization method chose the Genome count (estimated gene copies).

As functional profile of the dataset could be represents using different database for functional evidence, to get KO table based based on KEGG database, set the KO option for the Function item.

The source for searching will be the metagenomes previously selected. Prior to consider the total secuece annotated as metagenomes those sequences included in the assembled as the unassembled fraction must be selected. For that puropose in the Genome option set both (assembled and unassembled) and all finished, permanent draft and draft for MER-FS Metagenome and Sequencing status items respectively.

Finally press Go. A new screen will be appeared where the option for download the KO table will be shown. Finally select for Download tab-delimted file for Excel