VERSION 2

JUN 15, 2018

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.q2pdydn

Protocol Citation: Elaina ED Graham, Benjamin Tully 2018. Building Phylogenetic Tree. **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.q2pdydn>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
 We use this protocol and it's working

Created: Jun 15, 2018

Last Modified: Jun 15, 2018

PROTOCOL integer ID:
 13103

Building Phylogenetic Tree V.2

Elaina ED Graham¹, Benjamin Tully²

¹University of Southern California;

²Center for Dark Energy Biosphere Investigations

Elaina ED Graham
 University of Southern California

ABSTRACT

Making a Phylogenetic Tree

In this procedure we are going to build a phylogenetic tree! Throughout I'll refer to scripts available on my github here. We will be using the 16 ribosomal proteins used in Hug et al. 2016. The HMM models for these are available on my github in a file called `hug\_ribosomalmarkers.hmm`. We will be running this tutorial using the genomes and files found in the folder `Example`.

As an overview I will be explaining

1. How to generate gene predictions using prodigal for genomes of interest
2. How to identify ribosomal proteins using an hmm model
3. How to align, trim, and concatenate proteins for a phylogenetic tree
4. building a phylogenetic tree

To cite this workflow reference this paper:

Graham, E. D., J. F. Heidelberg, and B. J. Tully. 'Potential for primary productivity in a globally-distributed bacterial phototroph.' *The ISME journal* (2018)
 doi: <https://doi.org/10.1038/s41396-018-0091-3>

BEFORE START INSTRUCTIONS

Before Starting Be sure you have all the required Pre-Requisites.

Python2.7
BioPython
HMMER
Prodigal
BinSanity
Muscle
TrimAL
FastTree

See [this github page](#) for links to all dependencies.

To cite this workflow reference this paper:

Graham, E. D., J. F. Heidelberg, and B. J. Tully. 'Potential for primary productivity in a globally-distributed bacterial phototroph.' *The ISME journal* (2018)

doi: <https://doi.org/10.1038/s41396-018-0091-3>

Gathering the right files

1

Now to get all of the scripts and files do the command below to download the git repository.

The cd into `PhylogenomicsWorkflow/Example`

Command

This will clone the github repository to your local machine

```
$ git clone https://github.com/edgraham/PhylogenomicsWorkflow.git  
$ cd PhylogenomicsWorkflow/Example
```

Command

You should now be in the PhylogenomicsWorkflow/Example directory which contains Genomes of interest and a small set of reference ribosomal proteins pulled from genomes on NCBI

```
$ ls Genomes
unknown1.fna unknown2.fna unknown3.fna unknown4.fna unknown5.fna
$ ls HugRef
ExampleRefSet.RpL14.faa ExampleRefSet.RpL22.faa ExampleRefSet.RpL4.faa
ExampleRefSet.RpS17.faa
ExampleRefSet.RpL15.faa ExampleRefSet.RpL24.faa ExampleRefSet.RpL5.faa
ExampleRefSet.RpS19.faa
ExampleRefSet.RpL16.faa ExampleRefSet.RpL2.faa ExampleRefSet.RpL6.faa
ExampleRefSet.RpS3.faa
ExampleRefSet.RpL18.faa ExampleRefSet.RpL3.faa ExampleRefSet.RpS10.faa
ExampleRefSet.RpS8.faa
..
```

Generate Gene Calls and Extract Ribosomal Proteins from G.

2

The primary script in this workflow is `identifyHMM`. The script relies on the user providing the location of a file containing Hidden Markov Models (HMMs) for their genes of interest. Here we have provided you with a file called `hug_ribosomalmarkers.hmm`. This contains HMM models for 16 Ribosomal proteins: RpL14, RpL15, RpL16, RpL18, RpL22, RpL24, RpL2, RpL3, RpL4, RpL5, RpL6, RpS10, RpS17, RpS19, RpS3, RpS8.

Now you should enter the directory containing your genomes (in our case `/PhylogenomicsWorkflow/Example/Genomes`)

The help message for `identifyHMM` is given below.

```
usage: identifyHMM [-h] [--markerdb MARKERDB] [--performProdigal]
[--cut_tc] [--outPrefix OUTPREFIX] [--Num NUM]
[-E E]
Input Identify marker genes in in
protein sequences of genomes. positional arguments: Input
Target file(s). Provide unifying text of desired
genome(s). Ext must be 'fna' or 'faa'. optional arguments: -h, -
-help show this help message and exit --markerdb
MARKERDB Provide HMM file of markers. Markers should have a
descriptive ID name. --performProdigal Run Prodigal on input
genome nucleotide FASTA file --cut_tc use hmm
profiles TC trusted cutoffs to set all
thresholding --outPrefix OUTPREFIX
Provide prefix of names for marker output files. -E E
Set E-Value to be used in hmmsearch. Default: 1E-5
```

****Note**** When using `identifyHMM` on your own data you need to remember that you should be in the directory containing your MAGs when you run the program and ensure that the only genomes in this directory are the genomes of interest. The program will parse through every file with the suffix given as the [input]. So in this case our input is `.fna`. Second, if you want to run identifyHMM with your own gene calls you will want to exclude the `--performProdigal` flag and be sure that your gene calls end with the suffix `.faa` and are in the same directory as the genomes of interest.

The HMM file that we will be using is found in
`/PhylogenomicsWorkflow/hug\_ribosomalmarkers.hmm` on the github. The HMM Models in this file were pulled from PFAM and represent 16 ribosomal proteins that tend to be syntenic/co-located ([Hug et al. 2016](#))

Once in the `Genomes` directory run `identifyHMM` as Follows:

```
identifyHMM --markerdb ../../hug_ribosomalmarkers.hmm --
performProdigal --cut_tc --outPrefix HUG .fna
```

The output of this will be 16 `.faa` files appended with the prefix spefied by `--outPrefix` (in this case we used `HUG`), five `.faa` files corresponding to the prodigal gene calls, and five hmm reports (Stored in the `.tbl` files). So the files that look like `HUG\_RpL14.faa` are ribosomal proteins pulled from your genomes of interest.

```

hmmsearchc-log.txt  HUG_RpL16.faa  HUG_RpL24.faa  HUG_RpL4.faa
HUG_RpS10.faa      HUG_RpS3.faa   unknown1.fna    unknown2.fna
unknown3.fna        unknown4.fna    unknown5.fna    HUG_RpL14.faa
HUG_RpL18.faa      HUG_RpL2.faa   HUG_RpL5.faa    HUG_RpS17.faa
HUG_RpS8.faa        HUG_RpL15.faa  HUG_RpL22.faa   HUG_RpL3.faa
HUG_RpL6.faa        HUG_RpS19.faa  unknown1.faa    unknown2.faa
unknown3.faa        unknown4.faa
unknown5.faaunknown1.ribomarkers.tbl  unknown2.ribomarkers.tbl
unknown3.ribomarkers.tbl  unknown4.ribomarkers.tbl
unknown5.ribomarkers.tbl

```

Command

The output of this will be 16 `.faa` files appended with the prefix specified by `--outPrefix`, 5 `.faa` files corresponding to the prodigal gene calls, and 5 hmm reports (Stored in the `.tbl` files). So the files that look like `HUG_RpL14.faa` are ribosomal proteins pulled from your genomes of interest.

```

identifyHMM --markerdb ../../hug_ribosomalmarkers.hmm --performProdigal --cut_tc --
outPrefix HUG --Num 16 .fna

```

Merge Reference Proteins with Yours

- Now that we have extracted marker genes from our genomes of interest we can merge together the Ribosomal Protein calls we just made on our genomes of interest with those in the folder

```
'/PhylogenomicsWorkflow/Example/HugRef'
```

accordingly.

To do this we will use a quick bash trick that uses the text file `hug_marker_list.txt` which contains a list of the marker proteins we are searching for. Use the following Bash command:

Command

```
while read p do cat ../HugRef/ExampleRefSet.
```

Align

4

Now that we have 16 files containing Ribosomal proteins from our 5 unknown genomes and 100 references we can move on to aligning our proteins.

To align our proteins we can use muscle (You could also alternatively use [MAFFT](#)).

```
Dataset1_RpL14.faa Dataset1_RpL24.faa Dataset1_RpL6.faa
Dataset1_RpS8.faa Dataset1_RpL15.faa Dataset1_RpL2.faa
Dataset1_RpS10.faa hmmsearch-log.txt Dataset1_RpL16.faa
Dataset1_RpL3.faa Dataset1_RpS17.faa HUG_RpL14.faa
Dataset1_RpL18.faa Dataset1_RpL4.faa Dataset1_RpS19.faa
HUG_RpL15.faa Dataset1_RpL22.faa Dataset1_RpL5.faa
Dataset1_RpS3.faa HUG_RpL16.faa HUG_RpL18.faa HUG_RpL4.faa
HUG_RpS19.faa unknown1.ribomarkers.tbl HUG_RpL22.faa
HUG_RpL5.faa HUG_RpS3.faa unknown2.faa HUG_RpL24.faa
HUG_RpL6.faa HUG_RpS8.faa unknown2.fna HUG_RpL2.faa
HUG_RpS10.faa unknown1.faa unknown2.ribomarkers.tbl
HUG_RpL3.faa HUG_RpS17.faa unknown1.fna unknown3.faa
unknown5.faa unknown5.fna unknown5.ribomarkers.tbl
```

We will use the same trick as above where we feed the list of ribosomal markers in `hug\_marker\_list.txt` into a bash loop that runs muscle on head of the protein fasta files we generated. This will end in 16 alignment (`.aln`) files.

Command

```
while read p do muscle -maxiters 16 -in Dataset1_
```

Trim

- 5 Now that we have our alignments we need to trim those alignments. There are many programs that do this and I implore you to try a couple and see how different ones work, or even try manual trimming. Here we will use Trimal because its automated and works quickly when running alignments with lots of sequences.

You can run the following to trim your alignments:

Command

```
while read p do trimal -automated1 -in Dataset1_
```

Concatenate Proteins

- 6 Now that you have the trimmed and aligned sequences you can concatenate these 16 files. To do this we will use the concat script packaged with [BinSanity](#).

Usage is shown below:

```
usage: concat -f directory -e Alignment Extension --Prefix file
linker -o output
*****
*****
*****BinSanity*****
*****
*****      **      The `concat` script is used to concatenate
multiple sequence      **      **      alignments for conducting a
phylogenomic analysis. Note that you      **      **      receive an
error if there are any duplicate sequence ids in an      **      **
alignment.
*****
***** optional arguments:  -h, --help  show this help
message and exit  -f          Specify directory where alignments
are  -e          Specify the extension for your alignments (must
be in Fasta format)  --Prefix  Specify the prefix that links
your alignments (ex: if you have two alignments TOBG_RpL10,
TOBG_RpL24, the --Prefix would be TOBG  -o          Specify output
file  -N          Specify the minimum number of sequences needed
to be included in concatenation
```

Command

```
concat -f . -e .trimmed.aln --Prefix Dataset1 -o Dataset1.HugRibosomal.trimmed.concat.aln -N
8
```

Build the Tree

- 7 You now have a concatenated alignment 'Dataset1.HugRibosomal.trimmed.concat.aln' which can be used to build a phylogenetic tree.

We will be using FastTree with the `-gamma` and `-lg` parameters. These parameters are optional and just indicate what models we would like to use for branch length calculation and amino acid evolution respectively. Feel free to adjust these for your own purposes.

Command

```
FastTree -gamma -lg Dataset1.HugRibosomal.trimmed.concat.aln >  
Dataset1.HugRibosomal.trimmed.concat.newick
```

View Tree!

8

Now you have a newick file which can be viewed in a variety of tree views and edited. One of my favorite tools for making publication quality trees is [ITOL](#)!

To cite this workflow reference this paper:

Graham, E. D., J. F. Heidelberg, and B. J. Tully. 'Potential for primary productivity in a globally-distributed bacterial phototroph.' *The ISME journal* (2018)