MAR 31, 2020

🌐 Data Processing and Preparation of MALDI IMS data

Nathan Heath Patterson¹, Elizabeth Neumann¹, Jamie Allen¹, Danielle Gutierrez¹, Jeff Spraggins¹

¹Vanderbilt University

VU Biomolecular Multimodal Imaging Center / Spraggins Research Group

Human BioMolecular Atlas Program (HuBMAP) Method Development

Jamie Allen
Vanderbilt University

ABSTRACT

Scope:

How to process a mass spectrometry imaging data into a final imzML file.

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.bed3ja8n

Protocol Citation: Nathan Heath Patterson, Elizabeth Neumann, Jamie Allen, Danielle Gutierrez, Jeff Spraggins 2020. Data Processing and Preparation of MALDI IMS data. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.bed3ja8n>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: Mar 31, 2020

Last Modified: Apr 08, 2023

PROTOCOL integer ID:
34971

Keywords: HuBMAP, BIOMIC, Vanderbilt, Data Processing, MALDI IMS

- 1 For each spectrum in the data set, apply total ion current normalization by dividing the intensity values in the spectrum by the sum of the spectrum's intensity values.
- 2 Generate a mean spectrum for the dataset by taking the mean of each mass bin of the dataset.
- 3 Internally recalibrate the mean spectrum using well-known, spectrally ubiquitous lipid species, retaining the calibration equation.
- 4 Extract peak intensity data for every pixel using the provided identified mass list generated here (Lipid Annotation of MALDI IMS Datasets) by inverting the calibration coefficients to get the mass values in the original calibration and pulling intensity values from the Bruker .sqlite file that match these mass values.
- 5 Process the extracted peak list into a data table of columns: x, y, m/z 1, m/z 2, m/z 3... where 1, 2, and 3 are placeholders for the identified lipid species.

- 6 Read this table into R and create a *Cardinal* **MSImagingExperiment** object from the pixel coordinates and peak intensity values.
<https://cardinalmsi.org>
- 7 Use *Cardinal*'s `writelmzML()` function to write the **MSImagingExperiment** object to an `lmzML` file.