AUG 05, 2020

Database Preparation and Search for Protein Identification

avinash.kale¹

¹domnic colvin

UM-DAE Centre for Excellence in Basic Sciences

avinash.kale

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.bjdwiki7e

Document Citation: avinash.kale 2020. Database Preparation and Search for Protein Identification.

protocols.io

<https://dx.doi.org/10.17504/protocols.io.bjdwiki7e>

License: This is an open access document distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Created: Aug 05, 2020

Last Modified: Aug 05, 2020

DOCUMENT integer ID:

40086

Database Preparation and Search for Protein Identification

The mass-spec data were searched against the customized mosquito larvicidal toxin database which included well established larvicidal toxins like Cry1 to Cry73, Bin-A/B, VIP-1/2/3/4, and Mtx-1/2/3. (28). The default search parameters used for the analysis are as follows: (a) trypsin as the proteolytic enzyme with up to one missed cleavage; (b) peptide mass error tolerance of 20ppm; (c) fragment mass error tolerance of 0.1 Da; (d) carb-amidomethylation of cysteine as fixed modification (e) oxidation of methionine as a variable modification. A false discovery rate of 1% was applied while identifying the peptide-spectrum matches. Two criteria used to report a

positive find, 1) reported protein/toxin should have least two numbers of peptides in amino acid sequence; and 2) the length of each of the identified peptide sequences using LC-MS has a minimum of 10 amino acids.