

Apr 09, 2024

Version 2

Descending Platform V.2

DOI

<https://dx.doi.org/10.17504/protocols.io.14egn3ko6l5d/v2>

daniel.dautan daniel^{1,2}, Per Svenningsson^{1,2}

¹Department of Clinical Neuroscience, Karolinska Institutet, 171 76 Stockholm, Sweden;

²Aligning Science Across Parkinson's (ASAP) Collaborative Research Network, Chevy Chase, MD 20815, USA



Jacquelyn Haytayan

Weill Cornell Medicine

Create & collaborate more with a free account

Edit and publish protocols, collaborate in communities, share insights through comments, and track progress with run records.

Create free account

OPEN  ACCESS



DOI: <https://dx.doi.org/10.17504/protocols.io.14egn3ko6l5d/v2>

Protocol Citation: daniel.dautan daniel, Per Svenningsson 2024. Descending Platform. **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.14egn3ko6l5d/v2> Version created by [Eileen Ruth Torres](#)

License: This is an open access protocol distributed under the terms of the **Creative Commons Attribution License**, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

We use this protocol and it's working



Created: February 22, 2024

Last Modified: September 23, 2024

Protocol Integer ID: 95635

Keywords: ASAPCRN, behavior, motor, descending platform behavioral test, motor function, degree grid path, grid, test

Funders Acknowledgements:

Aligning Science Across Parkinson's

Grant ID: 020608

Abstract

Behavioral test to assess motor function.

The test is using a custom made 45-degree grid path with a width of 5cm and a length of 45cm. The 15cm one side is oriented with a 45-degree angle. The grid is formed by metal mesh with a 0.5cm space between.

Materials

Horizontal grid: custom made 45-degree grid path with a width of 5cm and a length of 45cm. 15cm of one side is oriented with a 45-degree angle. The grid is formed by metal mesh with a 0.5cm space between.



- 1 Place the custom-made, metal mesh grid to have an angle of 45 degrees with the floor.
- 2 Place a camera above the grid to record the entire procedure. Here we use the Logitech C920 webcam and windows camera software.
- 3 Orient the grid to have the starting spot horizontal.
- 4 At the end of the platform, place the animal cage to provide a safe target.
- 5 Take the mouse out of its cage using a paper tube to avoid stress and gently place the mouse on the starting spot.
- 6 Allow the mouse to explore the starting spot for 2-3 minutes.
- 7 Gently push the mice towards the tilted part of the grid path.
- 8 As soon as the mouse's hindlimbs are crossing the separation between the starting spot and the tilted spot, leave the mouse alone.
- 9 As soon as the mouse reaches the cage, stop the camera and place the cage back into the ventilated rack.
- 10 Clean the platform with 50% ethanol solution to remove stress-related smells.
- 11 Using the video, record the time for each mouse to go from:
1- hindlimb cross the starting spot line to 2- hindlimb touch the cage on the bottom.
- 12 Using 5 randomly selected frames of the period the mice descend the platform, measure the distance between the hindlimb of the mice, average the result to get usable values.