SEP 24, 2019

🌐 Domestication of L0 parts for Loop type IIS (Bsal and SapI)

Eftychis Frangedakis¹, Marta Tomaselli², Marius Rebmann³,
Susana Sauret-Gueto³

¹University of Cambridge; ²University of Cambridge, Open Plant;

³Plant Sciences, University of Cambridge, OpenPlant

OpenPlant Project

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.4whgxb6

Eftychis Frangedakis
University of Cambridge, Plant Sciences

Protocol Citation: Eftychis Frangedakis, Marta Tomaselli, Marius Rebmann, Susana Sauret-Gueto 2019. Domestication of L0 parts for Loop type IIS (Bsal and SapI). **protocols.io** <https://dx.doi.org/10.17504/protocols.io.4whgxb6>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: Jun 28, 2019

Last Modified: Sep 24, 2019

PROTOCOL integer ID:
25257

- 1 Domestication of internal Bsal and SapI sites is necessary when a DNA sequence of interest contains an internal Bsal or SapI recognition site. For domestication, overlapping PCR can be

used. Briefly, the sequence can be amplified as two separate PCR fragments upstream (fragment 1) and downstream (fragment 2) the recognition site. The enzyme recognition site will form part of the reverse primer of fragment 1 and the forward primer of fragment 2, that will be specially designed with a single nucleotide mismatch to alter the recognition site (taking care to not alter amino acid composition if the region is protein coding). Amplification primers will also contain SapI recognition sites that will allow the two fragments to be ligated together into the pUAP-pe. For example if you need to domesticate the following sequence:

5'-atggcgtcaattagtgatgcgcagctgtgcctttgagc..... ctattccagatt**GGTCT-C**-
agccaatgcaactgaagggcgattatcacagaggggtgatggaaggactatataactaa-3'

(fragment 1: underlined sequence, BsaI recognition sequence: sequence in bold capital letters and fragment 2: italicized sequence), the primers to be designed are

Primer1: 5'-ga**GCTCTTC**gtctcgaatggcgtcaattagtgatgc-3',

Primer2: 5'-ta**GCTCTTC**g**C**gacc-aatctggaatag -3',

Primer3: 5'-ga**GCTCTTC**gtc**G**c-agccaatg.caactgaagggc-3', and

Primer4: 5'-ta**GCTCTTC**gtctcaaagcttagtatatagtccttccatc-3'

(SapI recognition sequence: sequence in bold capital letters, common syntax overhangs: underlined sequence and primer mismatch: sequence in bold underlined capital letter).

Primer1 and Primer4 are designed according to Level 0 parts primer design.