



Jun 10, 2024

Version 1

Genome assembly (Nanopore and Illumina reads) V.1

DOI

dx.doi.org/10.17504/protocols.io.kxygxywyol8j/v1

Rafael Rodrigues Ferrari¹, Thiago Mafra Batista¹

¹Universidade Federal do Sul da Bahia



Thiago Mafra Batista

Universidade Federal do Sul da Bahia

Create & collaborate more with a free account

Edit and publish protocols, collaborate in communities, share insights through comments, and track progress with run records.

Create free account

OPEN  ACCESS



DOI: <https://dx.doi.org/10.17504/protocols.io.kxygxywyol8j/v1>

Protocol Citation: Rafael Rodrigues Ferrari, Thiago Mafra Batista 2024. Genome assembly (Nanopore and Illumina reads). **protocols.io** <https://dx.doi.org/10.17504/protocols.io.kxygxywyol8j/v1>

Manuscript citation:

Ferrari RR, Batista TM, Zhou QS, Hilário HO, Orr MC, Luo A, Zhu CD. The Whole Genome of *Colletes collaris* (Hymenoptera: Colletidae): An Important Step in Comparative Genomics of Cellophane Bees. *Genome Biol Evol.* 2023 May 5;15(5):evad062. doi: 10.1093/gbe/evad062. PMID: 37075227; PMCID: PMC10159585.

License: This is an open access protocol distributed under the terms of the **Creative Commons Attribution License**, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited



Protocol status: Working

We use this protocol and it's working

Created: June 10, 2024

Last Modified: June 10, 2024

Protocol Integer ID: 101556

Keywords: long reads, nanopore reads, genome assembly, genome polishment, bioinformatics, genome assembly, nuclear genome, genome, nanopore, bacterial genome database, nanopore technology, illumina short read, using long read, read, short read, long read, assembled contig, using illumina

Abstract

This protocol offers detailed, step-by-step instructions for students and researchers to assemble nuclear genomes using long reads generated by Nanopore technology. Before assembling the genome, we will align the reads against a bacterial genome database to eliminate potential contamination. The assembled contigs will then be polished using Illumina short reads.

Troubleshooting

SEQUENCING QUALITY CHECK

1 ****LongQC (<https://github.com/yfukasawa/LongQC>)****

Prepare a .pbs file to run the analysis remotely on Sagarana

```
python /home/fafinha/bin/LongQC/longQC.py sampleqc -x ont-ligation
-c /tmp/LongQC_run/reads_trim.fq \
-p 64 -o /tmp/LongQC_run
/home/fafinha/colletes_collaris/reads/genomic_reads/longreads_rawd
ata_collaris.fq

mv /tmp/LongQC_run/ /home/fafinha/colletes_collaris/
```

CROSS-SPECIES CONTAMINATION FILTERIN

2 ****Magic-BLAST (<https://ncbi.github.io/magicblast/>)****

Index the database

```
$~/bin/ncbi-magicblast-1.7.0/bin/makeblastdb -in
refseq_release_215_bacteria.fna -dbtype nucl
```

ONT whole-genome sequencing

Prepare a .pbs file to run the analysis remotely on Sagarana

```
magicblast -db
/databases/ref_prok_rep_genomes_out20/ref_prok_rep_genomes \
-query
/home/fafinha/collaris/reads/genomic_reads/reads/genomic_reads/ONT
_longreads_rawdata_collaris.fq \
-out_unaligned ONT_longreads_unaligned_in_refseq_prok_collaris.fa
-num_threads 80 -infmt fastq -unaligned_fmt fasta > output.sam
```

Illumina whole-genome sequencing

Prepare a .pbs file to run the analysis remotely on Sagarana



```
magicblast -db
/databases/ref_prok_rep_genomes_out20/ref_prok_rep_genomes -query
/home/fafinha/collaris/reads/genomic_reads/Illumina_shortreads.R1.
fastq \
-query_mate
/home/fafinha/collaris/reads/genomic_reads/Illumina_shortreads.R2.
fastq \
-paired -no_discordant -infmt fastq -unaligned_fmt sam -
num_threads 128 \
-out_unaligned
/home/fafinha/collaris/mafra/descontamination/illumina_reads/illum
ina_unaligned_in_refseq_prok.sam \
-out
/home/fafinha/collaris/mafra/descontamination/illumina_reads/illum
ina_aligned_in_refseq_prok.sam
```

Convert output file

```
$/programs/samtools-1.12/bin/samtools view -Sb -@12
illumina_unaligned_in_refseq_prok.sam >
illumina_unaligned_in_refseq_prok.bam

$/programs/samtools-1.12/bin/samtools sort
illumina_unaligned_in_refseq_prok.bam -o
illumina_unaligned_in_refseq_prok_sorted.bam -@12

$/programs/samtools-1.12/bin/samtools fastq -1 paired1.fq -2
paired2.fq -n illumina_unaligned_in_refseq_prok_sorted.bam -@12
```

GENOME SIZE ESTIMATION

3 ****Jellyfish (<https://github.com/gmarcais/Jellyfish>)****

Counting k-mers

Prepare a .pbs file to run the analysis remotely on Sagarana



```
/programs/jellyfish/jellyfish-2.3.0 count -C -m 21 -s 10G -t 36
/home/fafinha/collaris/reads/genomic_reads/D2015099C_L4_304X04.R1.
fastq \
/home/fafinha/collaris/reads/genomic_reads/D2015099C_L4_304X04.R2.
fastq -o /home/fafinha/collaris/Jellyfish/reads.jf

/programs/jellyfish/jellyfish-2.3.0 histo -t 36
/home/fafinha/collaris/Jellyfish/reads.jf >
/home/fafinha/collaris/Jellyfish/reads.histo
```

****Size estimation****

/////STRATEGY #1: GenomeScope (on my PC)\\\\\\

Go to the directory where reads.histo is located

```
$/home/rafael/genomescope2.0/genomescope.R -i reads.histo -o
output -k 21
```

/////STRATEGY #2: R (on my PC)\\\\\\

Go to the directory where reads.histo is located

```
$R

$library ("findGSE")

$findGSE(histo="reads.histo", sizek=21, outdir="21mer")
```

GENOME ASSEMBLY

4 ******NextDenovo (<https://github.com/Nextomics/NextDenovo>)******

*****Prepare an 'input.fofn' file*****

```
$ls
/home/fafinha/collaris/reads/genomic_reads/ONT_longreads_rawdata_c
ollaris.fq > input.fofn
```

*****Prepare a 'run.cfg' file*****

```
[General]
job_type = local
job_prefix = nextDenovo
task = all
rewrite = yes
deltmp = yes
parallel_jobs = 24
input_type = raw
read_type = ont
input_fofn = /home/fafinha/collaris/NextDenovo_run/input.fofn
workdir = 01_rundir
```

```
[correct_option]
read_cutoff = 1k
genome_size = 300m
sort_options = -m 20g -t 8
minimap2_options_raw = -t 8
pa_correction = 3
correction_options = -p 15
```

```
[assemble_option]
minimap2_options_cns = -t 8
nextgraph_options = -a 1
```

Prepare a .pbs file to run the analysis remotely on Sagarana

```
/home/fafinha/bin/NextDenovo/nextDenovo
/home/fafinha/collaris/NextDenovo_run/run.cfg
```

4.1 GENOME ASSEMBLY STATISTICS

****scaffolds_stats****

Compare two runs and include the stats into a .txt

```
$scaffold_stats.pl -f run1/assembly.fasta run2/assembly.fasta -N 1
-t 1000 10000 | tee stats.txt
```

****BBMap (<https://jgi.doe.gov/data-and-tools/bbtools/bb-tools-user-guide/bbmap-guide/>)****



#BBMap is part of BBTools (<https://jgi.doe.gov/data-and-tools/bbtools/bb-tools-user-guide/>)

Run the script stats.sh using the main output produced by Flye (on my PC)

```
$bash /mnt/d/Genomics/bbmap/stats.sh in=nd.asm.fasta
out=nd.asm.fasta_stats.txt
```

****BUSCO (<https://busco.ezlab.org/>)****

Run BUSCO (using a docker)

```
$docker run --rm -e USERID=$UID -u $UID -v /home/rferrari:/home/rferrari/ -w
/home/rferrari/projetos/collaris/BUSCO_run/genome/post_polishment/NextDenovo/run4_
RF_final/SRs ezlabgva/busco:v5.2.2_cv1 busco -i
/home/rferrari/projetos/collaris/BUSCO_run/genome/post_polishment/NextDenovo/run4_
RF_final/SRs/genome.nextpolish.fasta -l hymenoptera_odb10 --augustus_species
Apis_mellifera -o run1 -m geno -c 12
```

#To see list of available reference datasets

```
$docker run --rm -e USERID=$UID -u $UID -v /home/rferrari:/home/rferrari/ -w
/home/rferrari ezlabgva/busco:v5.2.2_cv1 busco --list-datasets
```

GENOME POLISHMENT

5 ****NextPolish (<https://github.com/Nextomics/NextPolish>)****

Using only short reads

Prepare a 'sgs.fofn' file

```
$ls
/home/fafinha/collaris/reads/genomic_reads/Illumina_shortreads.R1.
fastq
/home/fafinha/collaris/reads/genomic_reads/Illumina_shortreads.R2.
fastq > sgs.fofn
```

Create a 'run.cfg' file

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
rerun = 3
parallel_jobs = 6
multithread_jobs = 5
genome = /home/fafinha/collaris/mafra/flye_run/run1/assembly.fasta
genome_size = auto
workdir = /home/fafinha/collaris/Nextpolish_run/01_rundir
polish_options = -p {multithread_jobs}

[sgs_option]
sgs_fofn = /home/fafinha/collaris/Nextpolish_run/sgs.fofn
sgs_options = -max_depth 100 -bwa
```

****Prepare a .pbs file to run the analysis remotely on Sagarana****

```
/programs/NextPolish_n005/nextPolish
/home/fafinha/collaris/Nextpolish_run/run.cfg
```

*****Using both short and long reads*****

****Prepare a 'sgs.fofn' file****

```
$ls
/home/fafinha/collaris/reads/genomic_reads/Illumina_shortreads.R1.
fastq
/home/fafinha/collaris/reads/genomic_reads/Illumina_shortreads.R2.
fastq > sgs.fofn
```

****Prepare a 'lgs.fofn' file****

```
$ls
/home/fafinha/collaris/reads/genomic_reads/ONT_longreads_rawdata_c
ollaris.fq > lgs.fofn
```

****Create a 'run.cfg' file****

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
rerun = 3
parallel_jobs = 8
multithread_jobs = 8
genome = /home/fafinha/collaris/mafra/flye_run/run1/assembly.fasta
genome_size = 300m
workdir =
/home/fafinha/collaris/NextPolish_run/run5/long_short_reads/01_run
dir
polish_options = -p {multithread_jobs}

[sgs_option]
sgs_fofn =
/home/fafinha/collaris/NextPolish_run/run5/short_reads/sgs.fofn
sgs_options = -max_depth 100 -bwa

[lgs_option]
lgs_fofn =
/home/fafinha/collaris/NextPolish_run/run5/long_short_reads/lgs.fofn
lgs_options = -min_read_len 1k -max_depth 100
lgs_minimap2_options = -x map-ont
```

****Prepare a .pbs file to run the analysis remotely on Sagarana****

```
/programs/NextPolish_n005/nextPolish
/home/fafinha/collaris/NextPolish_run/run5/long_short_reads/run.cfg
```