



May 15, 2020 Version 1

Installation instructions for RNA-seq analysis using a conda environment V.1

DOI

dx.doi.org/10.17504/protocols.io.bgffjtjn

Laise Moraes¹

¹Fundação Oswaldo Cruz / Instituto Gonçalo Moniz



Laise Moraes

Fundação Oswaldo Cruz / Instituto Gonçalo Moniz

OPEN  ACCESS



DOI: dx.doi.org/10.17504/protocols.io.bgffjtjn

Protocol Citation: Laise Moraes 2020. Installation instructions for RNA-seq analysis using a conda environment. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.bgffjtjn>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: May 15, 2020

Last Modified: May 15, 2020

Protocol Integer ID: 37063

Abstract

The purpose of this protocol is to define and provide instructions for creating a conda environment for phylogenetic analysis

Installing Miniconda

- 1 Open a terminal (Ctrl + Alt + T).
Create a directory called softwares to your HOME directory, switch to it and then download the 64-bit Python 3 Miniconda installer.
Install Miniconda quietly, accepting defaults.
After installation, remove the Miniconda installer from directory.
Set the Miniconda permanent PATH and update conda packages to the latest compatible version.

Command

```
mkdir $HOME/softwares
cd $HOME/softwares
wget https://repo.continuum.io/miniconda/Miniconda3-latest-Linux-
x86_64.sh
bash Miniconda3-latest-Linux-x86_64.sh -bfp $HOME/softwares/conda
rm Miniconda3-latest-Linux-x86_64.sh
export
PATH="$HOME/softwares/conda/bin:/usr/local/share/rsi/idl/bin:$PATH"
echo 'export
PATH="$HOME/softwares/conda/bin:/usr/local/share/rsi/idl/bin:$PATH" '
>> $HOME/.bashrc
conda update -y -n base conda
```

Creating conda environment

- 2 Create a YML file to build a phylogenetic analysis environment called rna-seq.

Command

```
cat > rna-seq.yml <<EOF
name: rna-seq
channels:
  - bioconda
dependencies:
  - bedtools
  - bioconductor-rdavidwebservice
  - bowtie2
  - bwa
  - cutadapt
  - fastqc
  - igv
  - multiqc
  - tophat
  - trimmomatic
  - samtools
  - star
  - subread
EOF
```

3 Create the environment from the phy.yml file

Command

```
conda env create -f rna-seq.yml
```