VERSION 1
MAY 28, 2018

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.qhvdt66

Protocol Citation: Frank O Aylward 2018. Introduction to calculating dN/dS ratios with codeml. **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.qhvdt66>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: May 28, 2018

Last Modified: May 28, 2018

PROTOCOL integer ID:
12565

Introduction to calculating dN/dS ratios with codeml V.1

Frank O Aylward¹

¹Virginia Tech

Frank O Aylward
Virginia Tech

ABSTRACT

This is short tutorial on one way to calculate dN/dS ratios between pairs of protein-coding nucleic acid sequences using codeml in the PAML package.

Code is intended for use on an Ubuntu 16.04 LTS OS, but it may work on other Unix or Unix-like systems.

The programs used in this tutorial are:

codeml in the PAML package. On a Ubuntu 16.04 LTS system it should be able to install this tool with "sudo apt install paml".
<http://abacus.gene.ucl.ac.uk/software/paml.html>

PAL2NAL. This is essentially a PERL script that you will want to have handy, either by putting it in the folder that you are working in or by putting it somewhere that is in your PATH. <http://www.bork.embl.de/pal2nal/>

clustal-omega. You should be able to install this with "sudo apt install clustalo" This is a nice amino acid and nucleic acid alignment program. For purposes here your choice of aligner is not critical, so if you prefer MAFFT or Muscle or something else you can continue using those. <http://www.clustal.org/omega/>

Get the files organized

- 1 When calculating dnds ratios, file organization and consistent formatting are key. This is because it is necessary to create amino acid alignments of proteins first, and then convert them to nucleic acid. For this to happen we need to have both amino acid and nucleic acid sequences in separate files, and the proteins and genes in those file need to have the exact same unique identifiers in their FASTA headers.

First we can download some pre-compiled data from GitHub:

```
git clone https://github.com/faylward/dnds
```

If you navigate into the dnds/ folder you should see three files, one amino acid FASTA file, one nucleic acid FASTA file, and one codeml manifest file.

Create an amino acid alignment

- 2 First we want to align the amino acid sequences using clustal omega. The command here is simple enough if we use default parameters:

```
clustalo -i cluster_1.faa -o cluster_1.aln.faa
```

The .aln.faa file should have the amino acid alignment we need.

Convert aa alignment to na alignment

- 3 Now we can use pal2nal to get a codon-based nucleic acid alignment. This is critical since we need to be sure the nucleic acid alignment is aligned codon-by-codon so we know when substitutions result in a synonymous or nonsynonymous amino change. If we had simply performed an alignment on the nucleic acid sequence, we could not be sure that every single codon was lined up for this kind of calculation.

```
pal2nal.pl cluster_1.aln.faa cluster_1.fna -output paml -nogap > cluster_1.pal2nal
```

Here we input the aligned amino acid sequences and the raw nucleic acid sequences. The flags '-output paml' indicates that we want the output format to be in paml format (for simplicity in subsequent steps). The '-nogap' flag indicates that we want to remove gaps and inframe stop codons, since those are not used in subsequent steps. Just type 'pal2nal.pl' for a full description of all of the options.

Run codeml

- 4 To run codeml all we need to do is type 'codeml' in the same folder that the codeml.ctl file is in. All of the options are in the codeml.ctl file. There are lots of different options here that are described in the PAML manual. The key ones here are:
- seqfile = cluster_2.pal2nal [this tells the program where to find the codon-aligned nucleic acid sequences]
 - outfile = codeml.txt [this tells the program where we want the output]
 - runmode = -2 [this indicates we want to perform pairwise comparisons]

Some codeml applications require a phylogenetic tree to be provided in .nwk format, but since we are doing pairwise comparisons here it is not required.

When we run codeml, the calculation may take around a minute to finish, and a large number of files will be created. The file codeml.txt is what we want though. We can parse results with the parse_codeml_output.py python script:

```
python parse_codeml_output.py codeml.txt
```

Note that not all gene-pairs will be printed out. This is because the script filters out all pairs for which dS was < 0.01 or > 2. Values < 0.01 indicate that we may not get a reliable estimate of dN/dS, since the sequences are so similar. dS values > 2 indicate that the sequences are quite divergent and multiple substitutions have likely occurred at most sites, so dN/dS estimates will again be compromised.

The overall workflow should provide results that look something like this:

```
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$ clustalo -i cluster_1.faa -o cluster_1.aln.faa
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$ pal2nal.pl cluster_1.aln.faa cluster_1.fna -output paml -nogap > cluster_1.pal2nal
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$ codeml
CODONML in paml version 4.8, March 2014
codon      106: AGT AGT AGT TCT TCC AGC AGT AGT TCG TCT TCA TCT TCA TCA TCA AGT TCT TCC TCT TCA TCT TCT TCT TCC TCT AGT AGT
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$ python parse_codeml_output.py codeml.txt
Gene_1 Gene_2 dnds dN dS
TARA_MED_MAG_00021..TARA_MED_MAG_00021_00000000004 TARA_ANW_MAG_00012..TARA_ANW_MAG_00012_00000000019 0.0855 0.0501 0.5862
TOBG_MED-761..96635_4 TOBG_MED-648..67387_10 0.0356 0.0393 1.1037
TOBG_SP-276..78332_28 TARA_RED_MAG_00002..TARA_RED_MAG_00002_00000000000 0.0839 0.0019 0.0230
TOBG_SP-3101..88438_30 TOBG_NP-977..27904_6 0.0792 0.0892 1.1262
TOBG_SP-4372..MHASMcontig_3166805_9 GCA_002327705.1_ASM232770v1..DCX001000093.1_8 0.0642 0.0521 0.8125
TOBG_SP-4372..MHASMcontig_3166805_9 GCA_002420465.1_ASM242046v1..DIHZ01000006.1_12 0.0652 0.0544 0.8346
TOBG_SP-4372..MHASMcontig_3166805_9 GCA_002471805.1_ASM247180v1..DKQR01000167.1_8 0.0642 0.0521 0.8125
frankylward@AYLHARD-9H6YHK2:~/tutorials/dnds$
```

The real power comes from estimating dN/dS from multiple genes across several genomes, and looking for overall trends. But that will be a tutorial for another day :)