OCT 07, 2020

🌐 Lipids annotation of Nano-DESI MSI datasets

yang1832¹, Julia Laskin¹

¹Purdue University

NanoDESI MSI Julia Laskin group Purdue

yang1832

ABSTRACT

Scope:

Annotate lipid species detected by Nano-DESI IMS analysis.

Expected Outcome:

A list of lipid identifications with low mass errors (<5 ppm) that correlate to ion images produced by Nano-DESI IMS analysis.

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.bm2qk8dw

Protocol Citation: yang1832, Julia Laskin 2020. Lipids annotation of Nano-DESI MSI datasets. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.bm2qk8dw>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: Oct 05, 2020

Last Modified: Oct 07, 2020

PROTOCOL integer ID:
42800

1 Create mass list from the averaged spectrum.

- 2 Use LIPIDMAPS database to annotate each m/z value with the following search criteria:
https://www.lipidmaps.org/resources/tools/bulk_structure_searches.php?database=COMP_DB
 - 1a. Positive Mode Adducts: [M+H]⁺, [M+Na]⁺, [M+K]⁺
 - 1b. Negative Mode Adducts: [M-H]⁻
 2. Specify Mass Tolerance: 0.005 m/z
 3. Specify Chains: Even Chains Only
- 3 Obtain DDA MS/MS data from each sample.
- 4 Calculate ppm error associated with each assignment and remove assignments with errors larger than 5 ppm, although most have errors lower than 3 ppm.
- 5 Use the diagnostic fragmentations and characteristic neutral loss to narrow down the peak assignment. Remove the assignments that does not match with the CID spectrum.