VERSION 2
JAN 08, 2019

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.wwwfe7e

Protocol Citation: Ken Youens-Clark, Bonnie L Hurwitz 2019. Login to UA HPC. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.wwwfe7e>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: Jan 08, 2019

Last Modified: Jan 08, 2019

PROTOCOL integer ID:
19094

Keywords: unix

Login to UA HPC V.2
Version 1 is forked from [ssh to UA HPC](#)

Ken Youens-Clark¹, Bonnie L Hurwitz¹

¹University of Arizona

Biosys-analytics

Tech. support email: kyclark@email.arizona.edu

Bonnie L Hurwitz
University of Arizona

ABSTRACT

This describes setting up ssh keys and configuration to avoid having to use your NetID+ 2-factor authentication every time you log into the HPC. Windows users will need to install a free Unix-like environment that provides a terminal so as to avoid using an ssh client like Putty (for example: Cygwin (<http://www.cygwin.com>)).

Cygwin users must be sure to install the 'ssh' tools which are not installed by default.

GUIDELINES

This protocol is designed for students at the University of Arizona. Students must have a netid to access the UA high-performance compute cluster for this protocol.

BEFORE START INSTRUCTIONS

You must have received access to the UA high-performance compute cluster by the instructor: Dr. Bonnie Hurwitz

1 Sign up for NetID+ <https://webauth.arizona.edu/netid-plus/>

2 Initial login

Open a terminal and type 'ssh <NetID>@hpc.arizona.edu'. Enter your NetID password and then follow the instructions for 2-factor authentication. You will be presented with a menu that says:

```
=====
HPC.ARIZONA.EDU
=====
```

Please select a target system to connect to:

```
(1) Ocelote
(2) El Gato
(Q) Quit
(D) Disable menu
```

Select "D" to disable the menu

Disabling menu...

3 Copy public key to speed up login

Open a second terminal on your */ocal*/machine and 'cd ~/.ssh'. If that directory does not exist, execute 'ssh-keygen' to create local keys; accept all defaults by pressing <Enter>. Then copy your *public* key:

```
$ cat ~/.ssh/id_rsa.pub
```

Copy and paste that text. On MacOS, you can use the 'pbcopy' (pasteboard copy) command:

```
$ pbcopy < ~/.ssh/id_rsa.pub
```

In the HPC terminal from your initial login (@gatekeeper), open '~/.ssh/authorized_keys' and add the line of text from the 'id_rsa.pub.' If the file does not exist, create it. Ensure that the permissions on the file are 600 ('chmod 600').

4 Test no-password login

Back in your */oca/*terminal, test that you can login without 2-factor auth by executing 'ssh <NetID>@hpc.arizona.edu'. If you were logged in automatically, you are all set.

5 Create login alias

In your */oca/*terminal, open '*~/.ssh/config*' and add the following lines:

```
Host hpc
  Hostname hpc.arizona.edu
  User <NetID>
```

Now on your local machine, you can "ssh hpc" to get a terminal on the HPC.