APR 18, 2021

🌐 Measure Effects of Manufacturing Variations of ENDS on coil Lifetime and Aerosol Generation

📁 In 1 collection

Qutaiba Saleh¹,

Edward C Hensel¹,

Nathan C. Eddingsaas¹,

Risa

Robinson¹

¹Rochester Institute of Technology

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.brsvm2n6

Protocol Citation: Qutaiba Saleh, Edward C Hensel, Nathan C. Eddingsaas, Risa Robinson 2021. Measure Effects of Manufacturing Variations of ENDS on coil Lifetime and Aerosol Generation. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.brsvm2n6>

MANUSCRIPT CITATION: Saleh, Q.M.; Hensel, E.C.; Eddingsaas, N.C.; Robinson, R.J. Effects of Manufacturing Variation in Electronic Cigarette Coil Resistance and Initial Pod Mass on Coil Lifetime and Aerosol Generation. *Int. J. Environ. Res. Public Health* 2021, 18, 4380. <https://doi.org/10.3390/ijerph1808438>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Respiratory Technologies Lab

Tech. support phone: +1 (585) 475-7684 email: RespTechLab@rit.edu

[Click here to message tech. support](#)

Qutaiba Saleh

Rochester Institute of Technology

ABSTRACT

Manufacturing variations in coil resistance, initial pod mass, and e-liquid color could have effects on the performance of electronic nicotine delivery system (ENDS). Specifically, these variations could affect coil lifetime, total particulate matter yield, and e-liquid consumption rate. This protocol is a step by step explanation of the test procedure used to assess these effects. The steps describe the preparation of test specimens, making measurements, and running puffing sessions on the device under test. While this protocol was used for Vuse ALTO ENDS, it was written in a way to make it as generic as possible so that it can be applied to other brands and types of ENDS. This protocol was successfully used in bigger research project. The article which this protocol is associated with will be added to the Metadata once it is published.

GUIDELINES

General capabilities:

- Familiar with handling electronic tobacco product for research purposes.
- Trained to work in the lab and dealing with sensitive equipment.
- Familiar with using Digital multi-meter (DMM) to make voltage, current, and resistance reading. It is important that the DMM used provides the option for four-wire resistance measurement. The DMM used in this protocol is a Keysight Model [34465A](#). This [link](#) is for the operating and service guide for 34465A.
- Familiar with using automatic puffing machine.
- Familiar with using accurate gravimeter.

MATERIALS

Protocol status: Working
We use this protocol and it's working

Created: Jan 11, 2021

Last Modified: Apr 18, 2021

PROTOCOL integer ID:
46165

Keywords: Electronic
Cigarette, Coil resistance,
Coil Lifetime, TPM,
Manufacturing Variation

- One ENDS device. This experiment use Vuse ALTO ENDS.
- 15 or more Vuse ALTO pods.
- Coil resistance testing apparatus. A step by step protocol to build this device can be found at:

CITATION

Qutaiba Saleh, Edward Hensel, Risa Robinson. Coil Resistance Testing Apparatus for VUSE ALTO. International Journal of Environmental Research and Public Health.

LINK

dx.doi.org/10.17504/protocols.io.bibnkame

The coil resistance testing device is also presented at:

Protocol

NAME

Coil Resistance Testing Apparatus for VUSE ALTO

CREATED BY

Qutaiba Saleh

PREVIEW

- A digital multimeter which is used with the coil resistance testing apparatus. In this experiment, we used 34465A KEYSIGHT™ Digital Multimeter. This is a [link](#) to the user manual.
- Automatic puffing machine to activate and run the ENDS under test to generate and collect aerosols. In this experiment, we used the previously validated Programmable Emissions System™ (PES™-1). Description of this machine can be found at:

CITATION

Hensel, E.C.; Jayasekera, S.; Robinson, R.J (2018). Accounting for effects of system dynamics to improve accuracy of emissions reported in e-cig vaping machines. Inhalation Toxicology.

LINK

<https://doi.org/10.1080/08958378.2018.1526232>

- Rubber tube to connect the mouthpiece of the pod to the inlet of the filter pad holder.

- Laboratory wrapping film to fix the tube to the mouthpiece. In this experiment, we used Bemis™ Parafilm™ M Laboratory Wrapping Film.
- Filter pads to collect aerosol. The types of the filter pad depends on the filter pad holder and the puffing machine used.
- A gravimeter. In this experiment, we used Mettler AE240 Analytical Balance gravimeter. The manual to this device can be found at this [link](#).
- A camera to document status of the pods under test.

SAFETY WARNINGS

- Use caution when handling of tobacco products.
- Avoid inhaling the aerosol which might be released when opening the filter pad holder or any other parts of the experiment setup.
- The temperature of the pod after use could be high especially after continuous and heavy use such as in this experiment.
- The aerosol materials collected on the pad holder could be toxic.
- The ENDS devices uses lithium batteries. It is important to use caution when working on the battery even if the battery is discharged. Short circuit connection between the battery terminals could cause fire.

BEFORE START INSTRUCTIONS

Assemble all the materials listed in the material page.

This protocol is for pod-style ENDS which typically consist of two user sub-assemblies.

The ENDS Pod is the removable pod which contains the heating coil, wick, e-liquid and mouthpiece.

The ENDS Power Control Unit (PCU) contains the battery, electronic circuitry and user interface.

Samples (pods) Preparation

- 1 Select the pods to be included in this experiment and execute all steps in this section on each pod.
- 2 Visually inspect the pod for any damage due to shipping, storage, or any other reason. Exclude

any pods with damages.

- 3 Document the UID for all pods.
- 4 Visually inspect the color of the e-liquid in the pods and classify the pods based on e-liquid color into Light or Dark. The pictures below gives examples of a pod with light e-liquid color and a pod with dark e-liquid color. If possible, the pods can be classified into more than two color groups.

Expected result

Vuse ALTO pod with light e-liquid.

Vuse ALTO pod with dark e-liquid.

- 5 Take a picture of the pod to document its color and undamaged status.

Before Conducting Puffing Session

- 6 Make sure the ENDS PCU is fully charged. If not, wait until it is fully charged before proceeding to the next step. This step is to eliminate the effects of variable battery level on ENDS performance. In this experiment, the ALTO ENDS was continuously connected to the charger while the ENDS was being used, as allowed by the manufacturer.

Safety information

The ENDS devices uses lithium batteries. It is important to use caution when working on the battery even if the battery is discharged.

- 7 Take “Before” reading for coil resistance using coil resistance testing apparatus. A protocol to build coil resistance testing apparatus for Vuse ALTO can be found using the link below.

CITATION

Qutaiba Saleh, Edward Hensel, Risa Robinson. Coil Resistance Testing Apparatus for VUSE ALTO. International Journal of Environmental Research and Public Health.

LINK

dx.doi.org/10.17504/protocols.io.bibnkame

- 8 Take "Before" pod (the e-liquid reservoir and coil) mass and filter pad mass using gravimeter.

Taking "Before" pod mass.

Taking "Before" filter mass.

- 9 Install the filter pad in the filter pad holder.

Steps for installing filter pad in the filter pad holder.

- 10 Connect the filter pad holder to its appropriate place in the emission system (PES-1 in this case).

CITATION

Hensel EC, Jayasekera S, Robinson RJ (2018). Accounting for effects of system dynamics to improve accuracy of emissions reported in e-cig vaping machines.. Inhalation toxicology.

LINK

<https://doi.org/10.1080/08958378.2018.1526232>

- 11 Install the ENDS pod in the ENDS PCU.
- 12 Connect the ENDS assembly to the emission system (PES-1 in this case). Use short connecting tube to connect the mouthpiece of the pod to the inlet of the filter holder. Use laboratory wrapping film to fix the tube to the mouthpiece.

ENDS assembly connected to the emission system using short connecting tube and wrapping film.

Run Puffing Session

- 13 Run trial based on the predefined puffing profile. The puffing profile used in this experiment consists of uniform square puffs with 18.33 mL/Sec flowrate, 5.5 Sec puff duration, and 11 Sec puff interval. Based on the amount of e-liquid remaining in the pod, the number of puffs per

session is selected to be 20, 10, or 5 puffs. This is to increase the precision at which coil lifetime is measured.

After Puffing Session

10s

- 14** Remove the ENDS assembly from the emission system within 00:00:05 of the conclusion of the trial. 5s
- 15** Remove the ENDS pod from the ENDS PCU and take "After" trial coil resistance measurement using the coil resistance test apparatus. This measurement should take place as soon as the session ends, this reading tries to assess coil resistance while it may still be warm due to usage.
- CITATION**
- Qutaiba Saleh, Edward Hensel, Risa Robinson. Coil Resistance Testing Apparatus for VUSE ALTO. International Journal of Environmental Research and Public Health.
LINK
dx.doi.org/10.17504/protocols.io.bibnkame
- 16** Remove the filter pad from the filter pad holder within 00:00:10 of the conclusion of the trial and take "After" reading for filter pad mass. 10s

Removing filter pad out of filter pad holder and placing it on the gravimeter to take "After" mass reading.

17 Take "After" reading for pod (the e-liquid reservoir and coil) mass measurement using gravimeter.

18 Document any other information relevant to the research question being investigated. It is always important to take notes of facts such as (droplets condensed on the connecting tube between pod and filter pad holder). Such notes could be critical in explaining anomalies and understanding the final result.

19 Assess coil resistance of the pod.

Expected result

If it is in the range of $\sim 0.7 - 2 \Omega$, coil was not damaged (functional). If it is increased to order of $400 \text{ k}\Omega$, coil was damaged (failed). These coil resistance ranges are for Vuse ALTO pods. Use appropriate values for other products.

Step 19 includes a Step case.

Functional

Coil resistance is between 0.7 and 2 Ω .

- 20 Assess the amount of e-liquid left in the pod to determine the number of puffs to be used in the next session trial. Profiles of 20, 10, 5 are used. As the amount of e-liquid in the pod was consumed, profiles with a smaller number of puffs are used. This was to increase the precision at which coil lifetime was measured. ➡ go to step #6 to conduct the next puffing session.

Result Analysis

- 21 Some of the important data points produced in this experiment can be organized in a table to simplified the later analysis as follows. The statistical mean and standard deviation can be also added to this table as applicable.

A	B	C	D	E	F	G	H
Pod ID	Initial Coil Resistance	Initial E-liquid Color	Initial Pod Mass	End Pod Mass	E-liquid Net Mass (Col. C - Col.D)	Coil Lifetime	Total Particulate Matter (TPM) per puff of First Session
Pod 1							
Pod 2							
.....							
.....							
Pod n							
Mean							
STD							

Key data points produced in this experiment.

- 22 In addition to the statistical mean and standard deviation which are already mentionedThe data in the table from the previous step can be analyzed test relations between the desired variables this experiment focuses on.
Next is a list some of the suggested correlation test:

- The correlation between initial coil resistance and coil lifetime.
- The correlation between initial coil resistance and initial TPM.
- The correlation between initial pod mass (or e-liquid net mass) and coil lifetime.
- The correlation between initial pod mass (or e-liquid net mass) and initial TPM.

The MATLAB functions [fitllim](#) and [corrcoef](#) can be used make these tests

T-tests can be conducted to test the effects of e-liquid color:

- T-test between coil lifetime of the pod with light e-liquid and dark e-liquid.
- T-test between TPM of the pod with light e-liquid and dark e-liquid.

The MATLAB function [ttest](#) can be used.

23

Further analysis can be conducted for more understanding of the data. Plots can be used to show the correlation of the experiment variables at the session level to explain their behavior. Some the the suggested plots are:

- Plot the coil resistance against the TPM at each session.
- Plot the coil resistance against pod mass at each session.
- Plot the pod mass against TPM at each session.

Expected result

The results of the experiment conducted using this protocol is presented in our article "Effects of Manufacturing Variation in Electronic Cigarette Coil Resistance and Initial Pod Mass on Coil Lifetime and Aerosol Generation". A link to the paper is presented in the Metatdata section of this protocol.