VERSION 2

OCT 11, 2017

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.j9bcr2n

External link:
https://github.com/shu251/QC_steps_V4_tagsequencing

Protocol Citation: Sarah K Hu 2017. Microbial eukaryotic 18S tag-sequence processing/QC - V4 region (automating). **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.j9bcr2n>

Microbial eukaryotic 18S tag-sequence processing/QC - V4 region (automating) V.2

Sarah K Hu¹

¹University of Southern California

Caron Lab - Protistan Ecology

Sarah K Hu

Woods Hole Oceanographic Institution

ABSTRACT

This protocol provides step-by-step instructions for implementing a perl script to easily automate quality checking of raw tag sequences. This was specifically constructed for the numerous 18S diversity projects (which target the V4 hypervariable specific for evaluating protistan diversity).

It is highly recommended that you follow along this Github repo: https://github.com/shu251/QC_steps_V4_tagsequencing

GUIDELINES

Protocol describes quality checking process for raw fastq sequences. Includes some discussion for alternate approaches. End product is ready for OTU clustering. I've also included suggestions for OTU clustering at the end (specific for 18S data). Much of this pipeline can be applied for any tag sequencing analysis, but keep in mind this was specifically constructed to analyze single-celled microbial eukaryotic communities.

This protocol (and my preferred method) is to perform as much quality checking on each individual sample before combining for downstream OTU clustering (or other analysis). This way, I can track any samples that may be not ideal for downstream analysis.

Full github repo: https://github.com/shu251/QC_steps_V4_tagsequencing

MANUSCRIPT CITATION:

Sarah K. Hu, Victoria Campbell, Paige Connell, Alyssa Gellene, Zhenfeng Liu, Ramon Terrado, & David A. Caron. Protistan diversity and activity inferred from RNA and DNA at a coastal ocean site in the eastern North Pacific. (2016). FEMS Microbiol Ecol. 92(4) doi: 10.1093/femsec/fiw050.

Sarah K. Hu, Zhenfeng Liu, Alle A. Y. Lie, Peter D. Countway, Diane Y. Kim, Adriane C. Jones, Rebecca J. Gast, S. Craig Cary, Evelyn B. Sherr, Barry F. Sherr, & David A. Caron. (2015). Estimating Protistan Diversity using High-throughput Sequencing. J Eukaryot Microbiol. 62(5): 688-693.

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: Oct 11, 2017

Last Modified: Mar 16, 2018

PROTOCOL integer ID:

8195

BEFORE START INSTRUCTIONS

Required programs:

- Database (preferably with associated taxa list) to align sequences to. A version of the PR2 database formatted for QIIME can be found [here](#)
- [QIIME](#) - v.1.9.1 or higher. Note as of Jan 2018 QIIME1 will not be supported. Future iterations of this protocol will use QIIME2.
- fastqjoin - this should install with QIIME. Alternatively you can use [PEAR](#) to merge PE sequences.
- [Trimmomatic](#) - v.0.32
- [vsearch](#) - v1.11.1
- Make sure you know your primer sequences and generate a fasta file: 'trimPE_V4primer.fasta'. In the below example I'm using [V4 Stoeck et al. 2010 primers](#)

Pre-processing

- 1 Input raw fastq files that are already demultiplexed. This tutorial uses V4 primers (Stoeck et al. 2010) for microbial eukaryotes

First create a text file with a list of file prefixes (prefix.txt).

Example:

Test01_L001_R1_001.fastq

Test01_L001_R2_001.fastq

Test02_L001_R1_001.fastq

Test02_L001_R2_001.fastq

Associated prefixes:

Test01

Test02

Programs required:

- Database (preferably with associated taxa list) to align sequences to. A version of the PR2 database formatted for QIIME can be found [here](#)
- [QIIME](#) - v.1.9.1 or higher. Note as of Jan 2018 QIIME1 will not be supported. Future iterations of this protocol will use QIIME2.
- fastqjoin - this should install with QIIME. Alternatively you can use [PEAR](#) to merge PE sequences.
- [Trimmomatic](#) - v.0.32
- [vsearch](#) - v1.11.1
- Make sure you know your primer sequences and generate a fasta file: 'trimPE_V4primer.fasta'. In the below example I'm using [V4 Stoeck et al. 2010 primers](#)
- Create a 'prefix.txt' file to index sample fastq files.
- Run 'create.map.pl'

https://github.com/shu251/QC_steps_V4_tagsequencing

Command

Clone github repo

```
git clone https://github.com/shu251/QC_steps_V4_tagsequencing
```

Create map file (for use in QIIME)

- 2 Map files in QIIME serve to de-multiplex reads (based on barcodes and indices) and are used in 'split_library' QIIME step. Here, I've split up the V4 forward primer to fulfill the necessary barcode / index space required in the QIIME mapping file. However, we aren't using this feature of the mapping file.

Use this QIIME command to check mapping file:

http://qiime.org/1.6.0/scripts/check_id_map.html

Command

```
#!/usr/bin/perl -w  
open INFILE,
```

Command

```
#Required the prefix.txt file  
./create.map.pl
```

Perl script to QC each fastq file

- 3** Steps of script noted here:
- (1) Import prefix file, named 'prefix.txt' and starting loop
 - (2) Remove primers using Trimmomatic
 - (3) Merge paired end (R1 and R2) reads with a 20 bp overlap
 - (4) Perform split library command in QIIME, filter sequences with Q score 30 (-q 29)
 - (5) Length filter: seqlength_cutoff.pl [input.fasta] [min] [max] [output.fasta]
 - (6) Chimera check with vsearch (uchime) using a reference database
 - You will need to acquire reference database that is best for your sample type. I am using the PR2 database. [You can download a QIIME formatted version here.](#)
 - Alternatively, you can change the command to run vsearch chimera checking de novo. This will take longer.
 - (7) Repeat and combine QCed reads together

Required components:

- Forward and reverse primer sequences, I'm using V4 Stoeck et al. 2010 primers
- reference database
- seqlength_cutoff.pl (see script abo)

Command

```
#!/usr/bin/perl -w  
open INFILE,
```

Check all steps

- 4
 - Run command below.
 - Output will generate a fasta file for each step of the QC process. This protocol (and my preferred method) is to perform as much quality checking on each individual sample before combining for downstream OTU clustering (or other analysis). This way, I can track any samples that may be not ideal for downstream analysis.
 - **Note:** for our lab, I see between 20-50% sequences lost per sample (from raw reads to post-chimera check). As long as the final sequence count is > 10,000 I keep the sample. Our threshold of at least 10,000 sequences (typically more) is very conservative.
 - Once this is done, you can clean up directory by removing any of these intermediate files.
 - **Explanation of output:** After running the count_seqs command (below), the output will show you the number of sequences in each step. We started with 800 sequences, initial quality trimming and primer removal/QC removed almost 200 sequences. Merging and additional QC removed 224 sequences, while length filtration removed no additional sequences. Finally, the chimera checking step only removed 69 sequences. We only kept around 40% of the total sequences.

Command

Example QIIME command to check number of sequences.

```
count_seqs.py -i  
Test01_L001_R1_001.fastq,Test01_L001_R2_001.fastq,Test01_trim_R1_PE.fastq,Test01_trim_  
R2_PE.fastq,Test01_trim_merged.fastq,Test01_trim_merged_Q30.fasta,Test01_trim_merged_  
Q30_len.fasta,Test01_trim_merged_Q30_len_nc.fasta
```

OTU-clustering

- 5 Depending on the questions you want to ask your data, decide about what type of OTU clustering you want to do (both algorithm and percent similarity).

QIIME is a great resource for tutorials on OTU clustering

- http://qiime.org/tutorials/otu_picking.html#running-the-otu-picking-workflows

Command

```
#OTU clustering with uclust, will make a new directory (pick_open)
pick_open_reference_otus.py -i allseqs_test.fasta -o pick_open -m uclust -r
/galadriel/sarah/PR2/pr2.qiime.fasta --suppress_step4 --suppress_taxonomy_assignment
cd pick_open
#assign taxonomy using PR2 database, creates a new directory (uclust_taxonomy)
assign_taxonomy.py -i rep_set.fna -t /galadriel/db/PR2/ids.names.2.txt -r
/galadriel/db/PR2/pr2.qiime.fasta -m uclust -o uclust_taxonomy
#make an OTU table, and convert to txt
make_otu_table.py -i final_otu_map.txt -o V4_tagseq_test.biom -t
uclust_taxonomy/rep_set_tax_assignments.txt
biom convert -i V4_tagseq_test.biom -o V4_tagseq_test.txt --to-tsv --header-key=taxonomy
```

Analysis

- 6 For examples of preliminary analyses and figure generation in R see:
https://github.com/shu251/PreliminaryFigures_V4_tagseq