JAN 03, 2019

Research on the application of mobile phone location signal data in earthquake emergency work

Xia Chaoxu¹

¹Institute of Geology China Earthquake Administration

Xia Chaoxu

ABSTRACT

After the earthquake, the important task of the earthquake emergency rescue work is to minimize casualties, but due to the sudden earthquake disasters, it is difficult to get enough disaster information immediately, especially the personnel distribution and movement information. The traditional method to obtain disaster data is through the earthquake report of the disaster area or the field investigation of the emergency rescue team, the work is lag and low efficiency. This paper analyzes the feasibility of mobile phone location signal data in earthquake emergency rescue work from several aspects, such as quantity, location, change rate, and epicentral distance. The results show that the mobile phone location signal data can quickly obtain the situation of the personnel distribution and quantity after the earthquake, we find the change rate, the distance, etc. can determine the approximate range of the earthquake impact field. Through the data distribution in different time periods, the movement of the personnel after the earthquake can be obtained. Based on several situations, we can obtain the basic situation of the disaster-stricken areas in time after the earthquake, especially the personnel relevant situation, and this data can provide a scientific basis for emergency rescue decision-making.

MATERIALS

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.wq4fdyw

Protocol Citation: Xia Chaoxu 2019. Research on the application of mobile phone location signal data in earthquake emergency work. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.wq4fdyw>

MANUSCRIPT CITATION:

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
 We use this protocol and it's working

Created: Jan 03, 2019

Last Modified: Jan 03, 2019

PROTOCOL integer ID:
 18940

Keywords: Jiuzhaigou
earthquake, emergency
rescue, mobile phone location
signal data, change rate

the distribution of signal data

- 1 We collected phone location data from Jiuzhaigou county, the time period of data acquisition is from 2 hours before the earthquake to 8 hours after the earthquake (19:00 on August 8th and 5:00 on August 9th), total 10 hours of data. In contrast, we also collected data for the same period on the day before the earthquake.

grid-processed;

- 2 the obtained number of mobile phone signals is grid-processed; the data in the grid is integrated and statistically analyzed. Through the analysis of the trend of the number of mobile phone signals in different periods, we get the change trends at different times (before the earthquake, when the earthquake hit, and after the earthquake) of the study area.

calculating the change rate

- 3 In this paper, we selected the data change rates of 21:09 (10 minutes before the earthquake), 21:19 (earthquake time), and 21:29 (10 minutes after the earthquake) to analyze. Where, N_a is the signal number of the previous stage, while N_b is the signal number of the later stage. When $\alpha < 0$, it means that the number of signals in the later phase is less than that in the previous phase. Conversely, when $\alpha > 0$, the signal number of the latter phase is greater than that in the previous phase.

The change rate of Overlap area data

- 4 For overlapping data, if the number of mobile phone signal data before an earthquake is the same as the number of signals at the time of an earthquake, it means that the personnel in the location have not changed or moved.

The change rate of Non-overlap area data

- 5 The other is non-overlapping data, the data or location before and after the earthquake is different (for example, at the same location, it has data before the earthquake but no data after the earthquake, or there is no data before the earthquake, but new data appears after the earthquake).

Data volume in relation to epicenter distance

- 6 Taking the epicenter as the center, we selected a buffer zone at a distance of 15km, 20km, 40km, and 80km from the epicenter, and we analyzed the change rate of signal data in different buffer zones. The change in signal data is relate to the change of time and the increase of distance.