VERSION 3

OCT 05, 2020

Rqtl_code V.3

G3: Genes|Genomes|Genetics

Anna Miller¹

¹Case Western Reserve University

Anna Miller

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.bmwtk7en

External link:

<https://doi.org/10.1534/g3.120.401824>

Document Citation: Anna Miller 2020. Rqtl_code.

protocols.io

<https://dx.doi.org/10.17504/protocols.io.bmwtk7en> Version created by [Anna Miller](#)

MANUSCRIPT CITATION:

Miller AK, Chen A, Bartlett J, Wang L, Williams SM, Buchner DA, A Novel Mapping Strategy Utilizing Mouse Chromosome Substitution Strains Identifies Multiple Epistatic Interactions That Regulate Complex Traits. G3: Genes|Genomes|Genetics 10(12). doi: [10.1534/g3.120.401824](https://doi.org/10.1534/g3.120.401824)

License: This is an open access document distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Created: Sep 30, 2020

Last Modified: Oct 05, 2020

DOCUMENT integer ID:

42675

```
##Install_rqtI
```

```
install.packages("qtl")
```

```
##load_package
```

```
library(qtl)
```

```
##Trait_data
```

```
mycross <- read.cross("csv", file = "trait_data.csv")
```

```
mycross <- jittermap(mycross)
```

```
mycross <- calc.genoprob(mycross, step=1.0, off.end=0.0, error.prob=1.0e-4, map.function = "haldane", stepwidth = "fixed")
```

```
mycross <- sim.geno(mycross, n.draws=10000, step = 1.0, off.end=0.0, error.prob=1.0e-4, map.function="haldane", stepwidth = "fixed")
```

```
##Covariate_sex
```

```
ac <- pull.pheno(mycross, c("sex"))
```

```
##Main_effect_sex
```

```
out.covar<- scanone(mycross, addcovar=ac, pheno.col=1, model = "normal", method = "hk")
```

```
out.covar.perm <- scanone(mycross,addcovar=ac, model="normal", method="hk", n.perm=10000)
```

```
summary(out.covar, perms=out.covar.perm, pvalues=TRUE)
```

```
##Epistatic_effect_sex
```

```
out.covar<- scantwo(mycross, addcovar=ac, pheno.col=1, model = "normal", method = "em")
```

```
out.covar.perm <- scantwo(mycross,addcovar=ac, model="normal", method="em", n.perm=10000)
```

```
summary(out.covar, perms=out.covar.perm, pvalues=TRUE)
```

```
##RNA_Seq
```

```
mycross <- read.cross("csv", file = "RNA_SEQ.csv")
```

```
mycross <- calc.genoprob(mycross, step=1.0, off.end=0.0, error.prob=1.0e-4, map.function = "haldane", stepwidth = "fixed")
```

```
mycross <- sim.geno(mycross, n.draws=10000, step = 1.0, off.end=0.0, error.prob=1.0e-4, map.function="haldane", stepwidth = "fixed")
```

```
##Covariate_sex
```

```
ac <- pull.pheno(mycross, c("sex"))
```

```
##Main_effect
```

```
operm1 <- scanone(mycross, addcovar=ac, method="hk", n.perm=10000)
```

```
n=1
```

```
c<-a <- scanone(mycross, pheno.col = 1, method = "hk")
```

```
for (n in 1:2180){
```

```
  a <- scanone(mycross, pheno.col = n, method = "hk")
```

```

c <- append(c,a)
n+1}
print(c)

##Epistatic_effect
operm2 <- scantwo(mycross, addcovar= ac, method="em", n.perm=10000)
n=1
c<-a <- scantwo(mycross, pheno.col = 1, method = "em")
for (n in 1:2180){
  a <- scantwo(mycross, pheno.col = n, method = "em")
  c <- append(c,a)
  n+1}
print(c)

##Visualizations
mname1 <- find.marker(mycross, chr=X, pos=X)
mname2 <- find.marker(mycross, chr=Y, pos=Y)

###Genotype Plot 1
plotPXG(mycross, pheno.col=1, c(mname1))

##Genotype Plot 2
plotPXG(mycross, pheno.col=1, c(mname2))

###Main Effect
thresh1 <- summary(out.covar.perm, alpha=c(0.05))
plot(out.covar, main= "Mainscan plot of GENE", ylim = c(0,6))
abline(h=thresh1, lty="dotted", lwd=1)

###Genotype Interactions
chr <- c("chrX", "chrY")
pos <- c(posx,posy)
qtl <- makeqtl(mycross, chr, pos, what="prob")
rqtl <- refineqtl(mycross, qtl=qtl, formula = y~Q1+Q2+Q1:Q2)
plotLodProfile(rqtl)

###Interaction effects
plotPXG(mycross, pheno.col=1, c(mname1, mname2))

###Context Dependent Genotype Effects
effectplot(mycross, pheno.col=1, mname1=mname1, mname2=mname2)

##LOD intervals
lodint(rqtl, qtl.index=2)

```

```
##Overall interaction RNA-Seq
library(tidyverse)
library(car)
library(rgl)
ggplot(data = RNA_SEQ_Plot) +
  geom_point(aes(x = RNA_SEQ_Plot$`Main 1`, y = RNA_SEQ_Plot$Epistatic), col = "midnightblue") +
  theme_bw() + xlim(0, 15) + ylim(0, 15) +
  labs(x = "Main Effect 1", y = "Epistatic")
ggplot(data = RNA_SEQ_Plot) +
  geom_point(aes(x = RNA_SEQ_Plot$`Main 2`, y = RNA_SEQ_Plot$Epistatic), col = "midnightblue") +
  theme_bw() + xlim(0, 15) + ylim(0, 15) +
  labs(x = "Main Effect 2", y = "Epistatic")
ggplot(data = RNA_SEQ_MAIN_EFFECTS_FOR_PLOTS_4_2) +
  geom_point(aes(x = RNA_SEQ_MAIN_EFFECTS_FOR_PLOTS_4_2$main_LOD, y =
RNA_SEQ_MAIN_EFFECTS_FOR_PLOTS_4_2$Epistatic P`), col = "midnightblue") +
  theme_bw() + xlim(0, 15) + ylim(0, 15) + labs(x = "Main Effect", y = "Epistatic")

##Circos Plot
library(circlize)
df <- circose_inr
circos.par("track.height" = 0.1)
circos.initialize(factors = df$chr, x = df$pos)
circos.track(factors = df$chr, y = df$pos, bg.col=c("blue", "red"),
  panel.fun = function(x, y) {
    circos.text(CELL_META$xcenter, CELL_META$cell.ylim[2] + uy(5, "mm"),
      CELL_META$sector.index)
    circos.axis(labels.cex = 0.6) })
circos.link(chr1,position,chr2,position,col = "color")
circos.link(chr1,position,chr2,position,col = "color")
```