Apr 11, 2019 Version 1

Spectral photogrammetry protocol V.1

DOI
dx.doi.org/10.17504/protocols.io.v52e88e

Aurore Mathys[1]

[1][Royal Museum for Central Africa], [Royal Belgian Institute of Natural Sciences]

Aurore Mathys

OPEN ACCESS

DOI: dx.doi.org/10.17504/protocols.io.v52e88e

Protocol Citation: Aurore Mathys 2019. Spectral photogrammetry protocol. **protocols.io** **https://dx.doi.org/10.17504/protocols.io.v52e88e**

Protocol status: Working
We use this protocol and it's working

Created: December 05, 2018

Last Modified: April 11, 2019

Protocol Integer ID: 18330

Acquisition

1 Place de specimen at the center of the turntable with scales, photogrammetry marker and MSI calibration card (CHSOS).

2 Setup lamp and camera distance. Place the camera at approximately 30°.

3 Setup the correct exposure for each wavelenght and verify that the exposure is correct in spectrashoot using the MSI calibration card. Adjust exposure until the specimen is correctly lit.

4 Start capturing: for one specimen position capture at all the 15 wavelengths + white light. Then add the UV-pass filter and capture pictures in the UV wavelengths (UVR). Next place the UV-cut off filter and capture picture for each UV wavelengths (UVF). Pictures should be capturated in raw format.

5 Rotate the turntable of 10° and repeat step 4. Do this for the complete rotation.

6 Move the camera at an angle of 60° at the approximately the same distance than previously and repeat the operation for the complete rotation.

7 If necessary turn the specimen and repeat the process for as many rotation/views as necessary.

Pre-processing

8 Separate the wavelengths in different folders.

Processing

9 Open Agisoft Photoscan and create a chunk for each wavelengths (rename the chunks accordingly). Import the pictures.

10 Go to workflow > batch process and add the following step: align pictures (highest), build dense cloud (high), build mesh (high).

11 Repeat the processing 3 times to make sure the results are reliable.

12 If the results are reliable, export the models as .stl for surface analysis.