VERSION 1

AUG 03, 2018

OPEN ACCESS

DOI:

dx.doi.org/10.17504/protocols.io.sbueanw

External link:

<https://www.liebertpub.com/doi/10.1089/3dp.2018.0060>

Protocol Citation: Anton Du Plessis 2018. Standard method for microCT-based additive manufacturing quality control 1: Porosity analysis.

protocols.io

<https://dx.doi.org/10.17504/protocols.io.sbueanw>

MANUSCRIPT CITATION:

A du Plessis, I Yadroitava, SG le Roux, I Yadroitsev, 'X-ray microcomputed tomography in additive manufacturing: a review of the current technology and applications', 3D printing and additive manufacturing. <http://doi.org/10.1089/3dp.2018.0060>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Standard method for microCT-based additive manufacturing quality control 1: Porosity analysis V.1

Anton Du Plessis¹

¹University of Stellenbosch

Anton Du Plessis

ABSTRACT

MicroCT is a well-established technique that is used to analyze the interior of objects non-destructively, and it is especially useful for void or porosity analysis. Besides its widespread use, few standards exist and none for additive manufacturing as yet. This is due to the inherent differences in part design, sizes and geometries, which results in different scan resolutions and qualities. This makes direct comparison between different scans of additively manufactured parts almost impossible. In addition, different image analysis methodologies can produce different results. In this method paper, we present a simplified 10 mm cube-shaped coupon sample as a standard size for detailed analysis of porosity using microCT, and a simplified workflow for obtaining porosity information. The aim is to be able to obtain directly comparable porosity information from different samples from the same AM system and even from different AM systems, and to potentially correlate detailed morphologies of the pores or voids with improper process parameters. The method is applied to two examples of different characteristic types of voids in AM: sub-surface lack of fusion due to improper contour scanning, and tree-like pores growing in the build direction. This standardized method demonstrates the capability for microCT to not only quantify porosity, but also identify void types which can be used to improve AM process optimization.

ATTACHMENTS

[01 Cube porosity Edit.mkv](#)

[Method for 10 mm cube porosity analysis.pdf](#)

Protocol status: Working
We use this protocol and it's working

Created: Aug 03, 2018

Last Modified: Aug 03, 2018

PROTOCOL integer ID:
14420

Keywords: additive
manufacturing, x-ray
tomography, microCT, image
analysis, porosity, quality
control