VERSION 1

OCT 20, 2019

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.8hzht76

Protocol Citation: Jorge Fernández 2019. Streptavidin immobilization stressed test. **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.8hzht76>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
 We use this protocol and it's working

Created: Oct 20, 2019

Last Modified: Oct 20, 2019

PROTOCOL integer ID:
 28953

Keywords: Jorge Fernández

Streptavidin immobilization stressed test V.1

Jorge Fernández¹

¹Universidad Complutense de Madrid

AEGIS - Madrid iGEM 2019

Laura Armero

ABSTRACT

The following protocol was performed to test the affinity of the protein streptavidin for the nitrocellulose when applied a continuous flow of solvent.

MATERIALS

MATERIALS

- nitrocellulose membrane sheets size 210 mm × 297 mm thickness 200 µm **Sigma Aldrich Catalog #Whatman® FF170HP Din A**
- Whatman® FF80HP Din A4 **Contributed by users Catalog #FF80HP DIN A4 10/pk**

Reagents:

- Ponceau 0.1% with in acetic acid 5%
- PBS-tween 0.1%
- Streptavidin 5 µm/ml
- dH₂O

Materials:

- Micropipette 0.2-2 µl
- Tape
- Desiccator
- Jar

BEFORE START INSTRUCTIONS

Make sure that the surfaces and materials are clean before start.

Cut the FF80HP nitrocellulose membranes in 2 rectangles of 0.8cm x 4 cm dimensions. Repeat

- 1 this procedure with the FF170HP nitrocellulose to obtain a total of 4 nitrocellulose pieces.
- 2 Stamp the microfluidic design, following the protocol microfluidic channels wax priming on:
 - One piece of the FF170Hp nitrocellulose membrane
 - One piece of the FF80HP nitrocellulose membrane.
- 3 Glue the absorbant pad with tape at the top edge top of the 4 pieces of nitrocellulose. the dimensions of the absorbant pad are 0.8 cm x 1.2 cm.
- 4 Deposit 0,33 ul of streptavidin solution with a micropipette. Repeat this procedure 3 times, letting the drop dry in between each time.
The procedure must be done in the 4 pieces of nitrocellulose.
- 5 Let the pieces dry overnight at 4°C in a desiccator.
- 6 Perform a thin-layer chromatography with PBS-Tween as the solvent: pour 15 ml of the solvent and position the pieces with the absorbant touching the bottom of the container.

Let the solvent flow trough the nitrocellulose for 15 min.

The assay can be done individually or with the 4 pieces of nitrocellulose at one time.
- 7 Let it dry at room temperature for 40 min
- 8 Reveal with Ponceau 0.1% within acetic acid 5% by immersing the nitrocellulose piece into the solution for a few seconds.
- 9 Destain in dH₂O in agitation for 2 min.