AUG 19, 2020

UAV DSLR photogrammetry with PPK processing

Oliver Lucanus¹, Margaret Kalacska¹

¹Applied Remote Sensing Lab, Department of Geography, McGill University

Canadian Airborne Biodiversity Observatory

Tech. support email: jocelyne.ayotte@umontreal.ca

Margaret Kalacska

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.bjm2kk8e

Protocol Citation: Oliver Lucanus, Margaret Kalacska 2020. UAV DSLR photogrammetry with PPK processing. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.bjm2kk8e>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working

Created: Aug 12, 2020

Last Modified: Aug 19, 2020

PROTOCOL integer ID:
40346

ABSTRACT

The following protocol details the steps needed to acquire UAV based photographs with a DSLR and generate geotags through a PPK workflow. The protocol requires the following equipment:

- DJI Matrice 600 Pro
- Ronin MX gimbal
- Canon 5D Mark III
- Emlid RS+
- Emlid M+/M2 with LoRa adaptor
- Pocket Wizard Multimax II intervalometer
- MiFi portable Wifi

In addition, a subscription to an NTRIP service (e.g. Smartnet NA https://www.smartnetna.com/coverage_network.cfm) and a portable wifi hub with a cellular plan are required.

Mission Planning

1 Steps for GS Pro 2.0 (v 2.0.12 at time of writing). This section is usually done days in advance of

the actual flight, but can be carried out in the field as well.

- 1.1 On iPad launch GS PRO
- 1.2 Click on "*My Missions*" and then the large + icon to create a new pre-planned mission
- 1.3 Select "*3D Map Area*"
- 1.4 Select "*Tap*" and follow instructions on screen to draw a polygon encompassing the area to be mapped
- 1.5 Define and edit area by moving corner points
- 1.6 Name mission "*Mission_name- horizontal*" where Mission_name is specific to the area of interest, for example *MerBleue-horizontal*
- 1.7 In the camera model menu scroll down to "*New Custom Camera*". Enter a name for the camera (e.g. Canon 5D Mark III 24). Input sensor width and height (in mm), sensor resolution width and height (# of pixels), focal length (in mm), and minimum and maximum shutter intervals (in sec).

For the 5D Mark III with the 24 mm lens set the resolution to 5760 px (W) x 3840 px (H), 36 mm (W) x 24 mm (H) and both shutter intervals at 2 seconds. Do not turn on the 35 mm equivalent toggle. Click *Update* to save and ensure it is the camera model selected.

- 1.8 Select shooting angle "*Course aligned*"
- 1.9 Select capture mode "*Equal distance interval*"
- 1.10 Select flight course mode "*Inside mode*"
- 1.11 Flight speed and shutter interval are automatically set
- 1.12 Set flight altitude (in meters AGL). With the Canon 5D Mark III and a 24 mm lens, 50 m altitude (and following the camera settings and processing instructions in the sections below results in 1.3-1.6 cm GSD and a ground footprint size of 75 m x 50 m). This link provides a GSD calculator from Pix4D: <https://support.pix4d.com/hc/en-us/articles/202560249-TOOLS-GSD-calculator>

File Home Insert Page Layout Formulas Data Review View Acrobat Tell me what you want to do...

Clipboard Font Alignment Number Conditional Formatting Table

C19:
$$=(C14*C16*100)/(C15*C17)$$

PIX4D

GROUND SAMPLING DISTANCE CALCULATOR

Instructions

1. Enter the Sensor Width (millimeters) in cell C14
2. Enter the Focal Length (millimeters) in cell C15 (real focal length, not 35 mm equivalent)
3. Enter the Flight Height (meters) in cell C16
4. Enter the Image Width (pixels) in cell C17
5. [Optional] Enter the Image Height (pixels) in cell C18
6. Hit Enter

Calculator

Sw	36	= the sensor width of the camera (millimeters)
Fr	24	= the focal length of the camera (millimeters)
H	50	= the flight height (meters)
ImW	5760	= the image width (pixels)
ImH	3840	= the image height (pixels)
GSD	1.30	= Ground Sampling Distance (centimeters/pixel)
Dw	75	= width of single image footprint on the ground (meters)
DH	50	= height of single image footprint on the ground (meters)

Dw = The footprint width / distance covered on the ground by one image in width direction

www.pix4d.com

GSD Calculator from Pix4D

1.13 Click the "Advanced" toggle

1.14 Set front and side overlaps to 80-90% such a high overlap is recommended because the camera is not triggered by the UAV and therefore, the position of the photographs is not as precise

1.15 Select a course angle that is parallel to one of the axes of the rectangular polygon denoting the area to be mapped

1.16 Set gimbal pitch to -90 degrees

1.17 Set End of Mission Action to "Hover"

1.18 In the information window under the mission name, swipe left to the second screen and note flight time and battery requirements. For large areas more than one set of batteries may be required.

1.19 Click the computer disk icon on top left of screen to save the mission

Initial course heading parallel to the long axis of the rectangle

1.20 Click left arrow "<" in the upper left corner of the screen to return to list of missions

1.21 Find the mission that was just created "Mission_name- horizontal", swipe left and select "Copy". Highlight the copied mission and click *Edit*

1.22 Rename this copied mission as "*Mission_name- vertical*"

1.23 Under the *Advanced* toggle rotate the course angle by 90 degrees.

Course angle has been rotated by 90 degrees

1.24 Click the computer disk icon to save the mission

UAV Preparation

- 2 The following steps apply to most UAV systems, but this protocol is written specifically for the use of a DJI Matrice 600 Pro. Use of a D-RTK system, while optional, greatly improves the UAV's accuracy and precision in following the pre-planned mission.

- 2.1 Ensure UAV batteries (multiple sets if necessary), flight controller, gimbal battery (or multiple batteries as needed) and iPad are fully charged. Charge overnight if necessary.

- 2.2 Ensure aircraft payload rating is capable of lifting the gimbal and camera weight if using a system other than the M600 Pro with a Ronin MX gimbal and Canon 5D Mark III with 24 mm lens.

- 2.3 Check weather and any new airspace restrictions that may be in place.

- 2.4 Onsite, prepare and mark home point (takeoff/landing site)

- 2.5 OPTIONAL: Set up D-RTK ground station on a tripod with a clear view of the sky and no nearby tall objects. Turn it on and wait for the LED on

- 2.6 Insert batteries into M600 Pro, turn on flight controller (make sure iPad is connected via USB cable to the controller) and then turn on the the UAV

- 2.7 Open DJI GO. Tap the System Status bar and select *Calibrate*. Follow the on-screen

instructions to

calibrate the compass. Then after successful compass calibration, turn the UAV off.

- 2.8** Mount the gimbal onto M600 Pro making sure to connect the CAN cable between the gimbal and the UAV and insert a gimbal battery.

Ground control point set up

- 3** While the use of GCPs and checkpoints is recommended whenever possible, there are circumstances where it may be logistically impractical or unsafe to do so. See <https://www.mdpi.com/2504-446X/4/2/13/htm> for a discussion on the implications of not including GCPs.

Consult: <https://www.pix4d.com/blog/why-ground-control-points-important> for details about GCP placement and number of GCPs to set out. Even if GCPs will not be used, aim to set out targets if possible to use as checkpoints to verify the accuracy of the final products.

- 3.1** If using GCPs and/or checkpoints set out targets in area to be mapped. Their location can be measured now in the workflow or after Section 8. Follow these steps to measure their position. The same Emlid RS+ unit that is being used as the base station (section 4) can be used, if not other unit is available.

- 3.2** Turn on MiFi, wait for MiFi to initialize before proceeding

- 3.3** Mount RS+ to a survey pole (2 m or taller)

- 3.4** Turn on RS+ and wait for all three lights to come on in sequence -> orange, blue, green. The blue light will start flashing rapidly as it joins the MiFi network. Once it has joined the network it will continue to flash slowly. This is what we want – we do NOT want the base to make its

own wifi network (solid blue light).

3.5 Connect cell phone to MiFi wifi network

3.6 Connect to RS+ via the Emlid Reach app on cell phone

3.7 Go to RTK tab and set mode to Static and GPS AR mode to Fix and Hold. Set GLONASS AR to ON. If it is not possible to get a good solution for the position by the end of this section, try setting the mode to Kinematic.

3.8 Leave default elevation (15 degrees) and SNR (35). These can be changed if it is not possible to get a good solution for the position by the end of this section

3.9 Set GNSS to GPS + GLONASS + SBAS @ 5 Hz

3.10 Go to Correction Input tab and ensure it is set to NTRIP and your credentials are entered. Click apply if you changed anything. Status should say connected. **This is why the base must be connected to the MiFi, rather than making its own network.

3.11 Go to Position Output tab and ensure it is turned OFF

3.12 Go to Base Mode tab and ensure it is turned OFF

- 3.13** Go to Bluetooth tab, ensure it is turned OFF
- 3.14** Go to the Status page – you should see mostly green bars for satellites in view with a corresponding grey bar for each (incoming NTRIP correction). If not, check the settings again.
- 3.15** Go to the Survey Tab and create a new project by clicking *New project*. Fill in Project name, Author and optionally, add comments.
- 3.16** Do not enable auto save rules, Click *Done* to processed to next step.
- 3.17** Press the "2 m" button (lower left of map) to change the default 2 m value to the height of the pole, press Save
- 3.18** Press the large + icon (lower right of screen) to move to next step
- 3.19** OPTIONAL: change default point name
-
- 3.20** Press *Collect* to start point collecting process. When a Fix is achieved, click Accept to save the location.
- 3.21** Move to next point and repeat 3.20. Continue until location of all points have been measured. Click the Back button to exist the collection window.

- 3.22** In the survey tab, under the project's name click the *Export* button and select Shp file. Email the downloaded file to yourself.
- 3.23** Turn off the RS+ via the software. The MiFi can be left on if proceeding to Section 4, otherwise turn off.

Emlid Base set up

4

- 4.1** Mount Emlid RS+ on a tripod in a location with a clear view of the hemisphere (as much as possible). Tall trees or other objects nearby will interfere with reception. Electronic devices may also affect the reception of the GNSS signal. Keep all electronics (except the MiFi) as far as possible from RS+ during data collection.

Source: <https://docs.emlid.com/reachrs/placement/>

- 4.2** Attach the LoRa antenna

4.3 Turn on MiFi, wait for MiFi to initialize before proceeding

4.4 Turn on RS+ and wait for all three lights to come on in sequence -> orange, blue, green. The blue light will start flashing rapidly as it joins the MiFi network. Once it has joined the network it will continue to flash slowly. This is what we want – we do NOT want the base to make its own wifi network (solid blue light).

4.5 Connect cell phone to MiFi wifi network

4.6 Connect to RS+ via the Emlid Reach app on cell phone

4.7 Go to RTK tab and set mode to Static and GPS AR mode to Fix and Hold. Set GLONASS AR to ON

4.8 Leave default elevation (15 degrees) and SNR (35). If at the end of this section you notice very low SNR because of your location you may need to reduce the SNR or elevation mask

4.9 Set GNSS to GPS + GLONASS + SBAS @ 5 Hz

4.10 Go to Correction Input tab and ensure it is set to NTRIP and your credentials are entered. Click apply if you changed anything. Status should say connected. **This is why the base must be connected to the MiFi, rather than making its own network.

- 4.11** Go to Position Output tab and ensure it is turned OFF
- 4.12** Go to Base Mode tab and ensure it is turned ON and set to LoRa. Set the base coordinates mode to Average Fix. Choose a reasonable time period ~15min should be sufficient. The longer you set this time the longer you need to wait before proceeding to the next section (M+/M2 set up).
- 4.13** Set output power to 20 dB and air rate to 9.11 kb/s (recommended). Select a frequency (e.g. 901 MHz) Record these values because the M+/M2 must be set to listen on these same settings.
- 4.14** Set RTCM messages as follows:
a. 1002 @ 1Hz
b. 1006 @ 0.1 Hz
c. 1010 @ 1 Hz
You can optionally turn on 1107 @ 1Hz and/or 1097 @ 1 Hz but it is usually not needed. RTK will not function if 1002 and 1006 are not turned on.
- 4.15** Go to Logging tab and **turn all three logs ON**. Failure to do so will result in having to collect the data over again. Check the logging period – by default new logs are started every 4 hrs.
-
- 4.16** Go to Bluetooth tab, ensure it is turned off
- 4.17** Go to the Status page – you should see mostly green bars for satellites in view with a corresponding grey bar for each (incoming NTRIP correction). If not, check the settings again.
- 4.18** Exit the Emlid Reach app on the phone and disconnect from the MiFi

- 4.19** Place MiFi on the ground nearby with screen facing DOWN, in a shaded location where it will not overheat.

Emlid M+/M2 set up

- 5** Ensure the M+/M2 will be powered independently from the gimbal during set up. Turning the gimbal on/off without properly shutting down the M2/M+ corrupts the settings and can corrupt its software if it loses power during its boot up/loading stage (i.e. before green light is solid). **Only after the camera is balanced and facing nadir should the USB cable be connected to the gimbal for power during flight (see steps below). The M600P should be outside with a clear view of the GPS antenna to the sky for this part.
- 5.1** Connect antenna cable to M+/M2
- 5.2** Connect LoRa transmitter and the M+/M2 is connected via the S2 port
- 5.3** Turn on the M+/M2 by plugging in the USB cable (powered by an external USB bank)
- 5.4** Orange, blue and green lights should come on in sequence. Solid blue means M+/M2 has made its own wifi network. *It is important the unit creates its own wifi network rather than connecting to a pre-existing one.*
- 5.5** Wait for a solid green light – this loads the software, does time sync, etc. Do not proceed until there is a solid green light on the unit.
- 5.6** Connect to its wifi network using phone with the Emlid Reach app installed. Default password is *emlidreach* DO NOT change this password

- 5.7 Go to the Correction Input tab and make sure the frequency, air rate and power settings match what was configured on the base unit
- 5.8 Go to RTK tab, make sure mode is set to Kinematic. Leave SNR mask (35) and elevation mask (15 degrees) as default.
- 5.9 For the M2 enable all GNSS at 5 Hz.
For the M+ enable ONLY GPS + GALILEO at 5 Hz
- 5.10 Go to Base mode tab, ensure it is OFF
- 5.11 Go to Position Output tab, ensure it is OFF
- 5.12 Go to Logging, ensure **all three logs are turned ON**. Failure to do so will mean having to do the data collection over.
- 5.13 Go to Status, you should see green and orange bars with grey ones next to them (incoming LoRa correction)
- 5.14 Turn off M2/M+ via the software

Camera and intervalometer set up

6

- 6.1** Ensure Canon 5D Mark III camera has a full battery
- 6.2** Ensure camera has a formatted SD card. Use minimum 1000x speed card, 2000x is better (minimum 32 GB). Slower cards will not work.
- 6.3** Remove lens cap and any filter that may have been installed on the lens. Set lens to 24 mm.
- 6.4** Turn camera on and Set to P mode
- 6.5** Set camera to acquire Raw only (not Raw + jpg), then turn the camera off.
- 6.6** Connect 3-pin Pocket Wizard remote control cable to camera
- 6.7** Mount camera on Ronin-MX gimbal

- 6.8** Connect other end of the remote control cable to the P2 port on the Multimax II intervalometer. DO NOT turn on the intervalometer yet
- 6.9** Balance the camera in a **horizontal position** (ensure it is balanced by turning on the gimbal and adjusting the motor stiffness as necessary). Then turn off the gimbal.
- 6.10** Turn on the M600P, then turn on the gimbal and using the M600P's remote control, turn the camera to face nadir. Leave the gimbal on from this step onwards.
- 6.11** Move the M600P to its takeoff location (should be turned off if it needs to be moved but the gimbal can remain on). GPS antennas need a clear view of the sky for all subsequent steps.
- 6.12** Connect the USB cable from the M+/M2 to the gimbal's USB port. As long as the gimbal is on, this step will turn the M+/M2 back on.
- 6.13** Connect the Emlid hotshoe adapter to the camera – **pins down**. The other end should be plugged into the C1 port of the M2/M+
- 6.14** Connect phone to the M2/M+ via its wifi (all three lights should be on and solid by now, if not, wait until they are to proceed)
- 6.15** Check that there are both green and/or orange satellite signal bars AND grey ones (incoming correction) on the status page of the Emlid Reach app. If not follow steps above to check the settings.
- 6.16** Go to the Logging tab and **make sure all logs are ON** **If the logs are not on data collection will need to be repeated**

- 6.17** Exit the Emlid app on the phone
- 6.18** Turn on the camera
- 6.19** Turn on the intervalometer (Tx mode)
- 6.20** Press *TEST* on the intervalometer to start triggering the camera. If it does not trigger the camera follow steps below to make sure it is set to infinite intervalometer mode with a 2 sec delay.
- 6.21** OPTIONAL STEP:
Only follow this step if Multimax II is not set up correctly to trigger the camera.
***/MENU A B** Activates camera shutter release at set interval for set number of activations. Set interval (amount of time between activations) in Hours:Minutes:Seconds to 2 sec, then set count to 0 for infinite count.

Photograph acquisition

7

- 7.1** If it is not already on, turn on flight controller (ensure iPad is connected), then turn on the UAV
- 7.2** Launch the DJI GO app, wait for system to initialize, ensure compass is calibrated and top

status bar is green "*Ready to Go*"

7.3

Click battery symbol, check each battery for equal cell voltage (within 2% capacity) and that all batteries are equally full. **DO NOT** continue if the batteries are not equally full.

7.4

Launch GS Pro, enter list of saved missions and select ""Mission_name- horizontal"

7.5

Click blue aircraft button on the top right corner of the screen

7.6

If pre-flight checks pass click "*Start to fly*". At this point the waypoints will be uploaded. Once that is complete the UAV will start the mapping mission. Monitor its progress and battery status during flight.

7.7

Once the mission is complete, take over manual control and land safely.

7.8

OPTIONAL: If the area to mapped is large and one battery set is not enough to complete the entire Mission_name- horizontal. Click the "Pause" button in GSPro during flight when the batteries are low (~30% capacity left). Take over manual control and land. Upon landing when it is safe to approach the UAV, hold the * key on the intervalometer to stop triggering the camera. Do not turn off the gimbal. Turn off the UAV and change the batteries. Turn the UAV back on. Press the TEST button on the intervalometer to resume triggering the camera. Follow steps 6.2, 6.3 and 6.4. Click the "Resume" button in GS Pro and finish acquiring the photographs.

7.9

When it is safe to approach the UAV hold the * key on the intervalometer to stop triggering the camera. Do not turn off the gimbal. Turn off the UAV and change the batteries. Turn the UAV back on. Press the TEST button on the intervalometer to resume triggering the camera. Follow steps 6.2, 6.3 and 6.4, except this time select "*Mission_name- horizontal*" and follow steps 6.5, 6.6 and 6.7.

Data retrieval

8 Follow these steps after landing – BEFORE turning anything off

8.1 Hold the * key on the Multimax II to cancel intervalometer

8.2 Turn off the Multimax II and the camera

8.3 Log into the M2/M+ via phone and the Emlid Reach app (connect to its wifi first). Go to the Logging tab and turn all logs off

8.4 Wait for logs to finish writing

8.5 Export each log one at a time and email them to yourself

8.6 Turn M2/M+ off via the app, then turn the gimbal and M600P off

8.7 Go to the RS+ base unit, connect to the MiFi and then log into the unit via the Emlid Reach app

- 8.8** Go to the Logging tab and turn all logs off. Wait for all the logs to finish processing, if the unit has been running for a long time it may take a few second to finish writing the logs.

- 8.9** Export all three logs and email them to yourself. Then turn RS+ off via the app and then turn MiFi off.

- 8.10** Remove SD card from camera and download photos. Make sure to download and keep ALL photos, even the ones of the ground before takeoff and after landing otherwise matching the event tags to the correct photo in post processing will be very difficult and inaccurate.

- 8.11** If not already done, measure the location of the GCPs and/or checkpoints as described in Section 3.

Geotag generation

9

These steps are nomally carried out in the laboratory, but could also be done in the field if there is access to a laptop with sufficient processing power. Check current hardware recommendations: <https://support.pix4d.com/hc/en-us/articles/202557289-System-requirements-Minimum-and-recommended-computer-specifications>

Software required:

- Adobe Lightroom (or other utility to convert .CR2 to large JPG with minimal compression)
- RTKLib (most recent version downloaded from the Emlid website)
- Pix4D Mapper

Optional software for troubleshooting:

- Exiftool

Additional data required:

- Commercial and/or NRCAN Active Control System base station data from a station near study site. Data are needed for the entire period of the data acquisition. Download in Rinex 3 format.
- Broadcast Ephemerides and Clock Corrections (from NRCAN ACS)

- 9.1 Convert ALL Canon .CR2 photographs to large JPGS in Adobe Lightroom. Ensure all metadata such as camera and lens info are retained.
- 9.2 Organize Emlid base station (RS+) and rover (M2/M+) files into separate folders
- 9.3 Organize the Commercial/NRCAN base station Rinex files, Broadcast Ephemerides and Clock Corrections files in a separate folder
- 9.4 Unzip the Commercial or NRCAN ACS base station data into a separate folder. When using SmartNet NA data each hour is provided as a separate zip file, unzip all files from all hours into the same folder.

Name	Date modified	Type	Size
qcvd214m.20g	8/11/2020 12:01 PM	20G File	18 KB
qcvd214m.20n	8/11/2020 12:01 PM	20N File	39 KB
qcvd214m.20o	8/11/2020 12:01 PM	20O File	6,637 KB
qcvd214m.htm	8/11/2020 12:01 PM	Chrome HTML Do...	81 KB
qcvd214n.20g	8/11/2020 12:01 PM	20G File	17 KB
qcvd214n.20n	8/11/2020 12:01 PM	20N File	45 KB
qcvd214n.20o	8/11/2020 12:01 PM	20O File	6,891 KB
qcvd214n.htm	8/11/2020 12:01 PM	Chrome HTML Do...	79 KB
qcvd214o.20g	8/11/2020 12:02 PM	20G File	18 KB
qcvd214o.20n	8/11/2020 12:02 PM	20N File	37 KB
qcvd214o.20o	8/11/2020 12:02 PM	20O File	6,817 KB
qcvd214o.htm	8/11/2020 12:02 PM	Chrome HTML Do...	78 KB
qcvd214p.20g	8/11/2020 12:02 PM	20G File	18 KB
qcvd214p.20n	8/11/2020 12:02 PM	20N File	44 KB
qcvd214p.20o	8/11/2020 12:02 PM	20O File	7,062 KB
qcvd214p.htm	8/11/2020 12:02 PM	Chrome HTML Do...	78 KB
qcvd214q.20g	8/11/2020 12:02 PM	20G File	17 KB
qcvd214q.20n	8/11/2020 12:02 PM	20N File	35 KB
qcvd214q.20o	8/11/2020 12:02 PM	20O File	7,080 KB
qcvd214q.htm	8/11/2020 12:02 PM	Chrome HTML Do...	81 KB
qcvd214r.20g	8/11/2020 12:02 PM	20G File	16 KB
qcvd214r.20n	8/11/2020 12:02 PM	20N File	42 KB

Base station files from Smartnet NA should be unzipped to a single folder

9.5 Launch rtkconv_qt.exe and select the Emlid base .UBX file for conversion

9.6 In the Options menu turn off the frequencies and GNSS systems not used

Options

RINEX Version: 3.03 ☐ Sep NAV Station ID: 0000 ☐ RINEX Name

RunBy/Obsv/Agency:

Comment:

Maker Name/#/Type:

Rec #/Type/Vers:

Ant #/Type:

Approx Pos XYZ: ☐ 0.0000 0.0000 0.0000

Ant Delta H/E/N: 0.0000 0.0000 0.0000

☒ Scan Obs Types ☐ Iono Corr ☐ Time Corr ☐ Leap Sec

Satellite Systems

☒ GPS ☒ GLO ☒ GAL ☐ QZS ☒ SBS ☐ BDS ☐ IRN

Excluded Satellites:

Observation Types: ☒ C ☒ L ☒ D ☒ S

Frequencies: ☒ L1 ☐ L2 ☐ L5/L3 ☐ L6 ☒ L7 ☐ L8 ☐ L9

Receiver options:

Time tolerance (s): 0.005 Debug: OFF

The RS+ is a single frequency (L1) system. **Click Convert**

9.7 Repeat the conversion process for the Emlid rover UBX file. Note the M+ is a single frequency (L1) system but the M2 is a dual frequency (L1 and L2) system.

9.8 Launch rtkpost_qt.exe. Select the files as shown below:

RTKPOST-QT ver.2.4.3 Emlid b33

☐ Time Start (GPST) ? ☐ Time End (GPST) ? ☐ Interval ☐ Unit

1/1/2000 00:00:00 1/1/2000 00:00:00 1 s 24 H

RINEX OBS: Rover ?

I:\CABO\2020\Emlid200801\Base\new_raw_202008011623.obs ...

RINEX OBS: Base Station

I:\CABO\2020\Emlid200801\Rinex\qcvd214*.20o ...

RINEX NAV/CLK, SP3, FCB, IONEX, SBS/EMS or RTCM

I:\CABO\2020\Emlid200801\Rinex\qcvd214*.20g ...

C:\Users\marga\Desktop\NRCAN\emr21166.sp3 ...

C:\Users\marga\Desktop\NRCAN\emr21166.clk ...

I:\CABO\2020\Emlid200801\Rinex\qcvd214*.20n ...

Solution ☐ Dir ...

I:\CABO\2020\Emlid200801\Base\new_raw_202008011623.pos ...

?

Plot... View... KML/GPX... Options... Execute Abort Exit

Note the input (i.e. Rover OBS) file is the output of the Emlid base UBX conversion. The Base Station file is the 'o' file from the unzipped SmartNetNA Rinex files. Replace the hour letter designation with a *. Repeat for the 'n' and 'g' files. Also select the clock and broadcast ephemerides files.

9.9 In the options tab, adjust the various options as shown below:

Options

Setting1 Setting2 Output Statistics Positions Files Misc

Positioning Mode Static

Frequencies / Filter Type L1 Combined

Elevation Mask (°) / SNR Mask (dBHz) 15 ...

Rec Dynamics / Earth Tides Correction ON OFF

Ionosphere Correction Broadcast

Troposphere Correction SBAS

Satellite Ephemeris/Clock Precise

☐ Sat PCV ☐ Rec PCV ☐ PhWU ☐ Rej Ed ☐ RAIM FDE ☐ DBCorr

Excluded Satellites (+PRN: Included)

☒ GPS ☒ GLO ☒ Galileo ☐ QZSS ☒ SBAS ☐ BeiDou ☐ IRNSS

Ext Opt... Load... Save... OK Cancel

When processing the Emlid base station position, the RTKLib Base Station should be set to RINEX Header Position if using Rinex files from NRCAN or Smartnet NA

9.10 Click **Execute** and wait for processing to finish

9.11 Click Plot and a window with the processed positions of the base station opens:

Display the .pos file

The large majority of positions should be quality level 1 (green) with a small spread.

9.12 Open the .pos file in Excel (space delimited)

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
1	%	program	:	RTKPOST-ver.2.4.3	Emlid	b33									
2	%	inp	file	:	I:\CABO\2020\Emlid200801\Base\raw_202008011623.obs										
3	%	inp	file	:	I:\CABO\2020\Emlid200801\Rinex\qcvd214*.20o										
4	%	inp	file	:	I:\CABO\2020\Emlid200801\Rinex\qcvd214*.20n										
5	%	inp	file	:	C:\Users\marga\Desktop\NRCAN\emr21166.sp3										
6	%	inp	file	:	C:\Users\marga\Desktop\NRCAN\emr21166.clk										
7	%	inp	file	:	I:\CABO\2020\Emlid200801\Rinex\qcvd214*.20g										
8	%	obs	start	:	8/1/2020 23:33.4 GPST	(week211 577413.4s)									
9	%	obs	end	:	8/1/2020 25:20.0 GPST	(week211 581120.0s)									
10	%	ref	pos	:	45.41422 -74.0255 8.0475										
11	%														
12	%	(lat/lon/h of			satellites)										
13	%	GPST	latitude(d	longitude	height(m)	Q	ns	sdu(m)	sde(m)	sdu(m)	sdne(m)	sdeu(m)	sdun(m)	age(s)	ratio
14	8/1/2020	23:33.4	45.43974	-74.2181	26.7265	1	11	0	0	0.0001	0	0	0	-0.61	2f
15	8/1/2020	23:33.6	45.43974	-74.2181	26.7265	1	11	0	0	0.0001	0	0	0	-0.41	2f
16	8/1/2020	23:33.8	45.43974	-74.2181	26.7265	1	11	0	0	0.0001	0	0	0	-0.21	2f
17	8/1/2020	23:34.0	45.43974	-74.2181	26.7265	1	11	0	0	0.0001	0	0	0	-0.01	2f

Sort based on the "Q" quality field and delete all non Q=1 rows

9.13

[illegible]

Save/write down the average base coordinates (keep all decimal places)

9.14

RTKPOST-QT ver.2.4.3 Emlid b33

☐ Time Start (GPST) ?
 ☐ Time End (GPST) ?
 ☐ Interval ☐ Unit

1/1/2000 00:00:00 1/1/2000 00:00:00 1 s 24 H

RINEX OBS: Rover ?

I:\CABO\2020\Emlid200801\Rover\new_raw_202008011654.obs ...

RINEX OBS: Base Station ?

I:\CABO\2020\Emlid200801\Base\new_raw_202008011623.obs ...

RINEX NAV/CLK, SP3, FCB, IONEX, SBS/EMS or RTCM

I:\CABO\2020\Emlid200801\Base\new_raw_202008011623.nav ...

C:\Users\marga\Desktop\WRCAN\emr21166.sp3 ...

C:\Users\marga\Desktop\WRCAN\emr21166.clk ...

| ...

Solution ☐ Dir ...

I:\CABO\2020\Emlid200801\Rover\new_raw_202008011654.pos ...

Note the clock and broadcast ephemerides files remain the same, but the Rover OBS file is that of the Emlid M+/M2 and the Base Station files (.obs and .nav) are the one created in the previous step.

9.15 Click on Options and set the options as shown below:

Options

Setting1 Setting2 Output Statistics Positions Files Misc

Positioning Mode Kinematic

Frequencies / Filter Type L1 Combined

Elevation Mask (°) / SNR Mask (dBHz) 15 ...

Rec Dynamics / Earth Tides Correction ON OFF

Ionosphere Correction Broadcast

Troposphere Correction SBAS

Satellite Ephemeris/Clock Precise

☐ Sat PCV ☐ Rec PCV ☐ PhWU ☐ Rej Ed ☐ RAIM FDE ☐ DBCorr

Excluded Satellites (+PRN: Included)

☒ GPS ☒ GLO ☒ Galileo ☐ QZSS ☒ SBAS ☐ BeiDou ☐ IRNSS

Ext Opt... Load... Save... OK Cancel

Note positioning mode is *kinematic* for the +/M2

The screenshot shows the 'Options' dialog box with the 'Positions' tab active. The 'Rover' section contains a dropdown for 'Lat/Lon/Height deg/m' and three input fields with values 0.000000000, 0.000000000, and 0.0000. Below this is a checkbox for 'Antenna Type (*: Auto)' and a 'Delta-E/N/U (m)' section with three input fields, all set to 0.0000. The 'Base Station' section has a similar dropdown and three input fields with values 45.439737780, -74.218128410, and 26.7270. A blue checkmark is drawn over these values. Below the Base Station section is a 'Station Position File' field and a button with three dots. At the bottom are buttons for 'Ext Opt...', 'Load...', 'Save...', 'OK', and 'Cancel'.

Enter the average Emlid base position calculated in Excel

9.16 Click Execute and wait for processing to finish

9.17 When processing is finished, click on Plot. The flight path of the UAV will be shown as logged by the M+/M2.

9.18 In the Plot window click on *File-> Open Solution 2* and select the “events” file

Name	Date modified	Type	Size
new_raw_202008011654.pos	8/11/2020 12:26 PM	POS File	1,035 KB
new_raw_202008011654_events.pos	8/11/2020 12:26 PM	POS File	68 KB

9.19 In the Plot window turn off Solution 1, keeping only Solution 2 which show the geotags for each photograph

Most of the positions should be quality level 1

9.20

Open the *events.pos* file in a text file viewer such as Notepad++, each row is the position information for a photograph. When using SmartNet NA as the original base station and as NTRIP provider during acquisition the coordinates are in NAD83CSRS datum and CGVD2013 ellipsoidal height

```

1 | program : RTKPOST-QT ver.2.4.3 Emlid b33
2 | % GPST
3 | % inp file : I:\CABO\2020\Emlid200801\Rover\new_raw_202008011654.obs
4 | % inp file : I:\CABO\2020\Emlid200801\Base\new_raw_202008011623.obs
5 | % inp file : I:\CABO\2020\Emlid200801\Base\new_raw_202008011623.nav
6 | % inp file : C:\Users\marga\Desktop\NRCAN\emr21166.sp3
7 | % obs start : 2020/08/01 16:54:53.4 GPST (week2116 579293.4s)
8 | % obs end : 2020/08/01 17:19:43.8 GPST (week2116 580783.8s)
9 | % ref pos : 45.439737780 -74.218128410 26.7270
10 | %
11 | % (lat/lon/height=WGS84/ellipsoidal,Q=1:fix,2:float,3:sbas,4:dgps,5:single,6:ppp,ns=# of satellites)
12 | % GPST latitude(deg) longitude(deg) height(m) Q ns sdn(m) sde(m) sdu(m) sdne(m) sdeu(m) sdun(m) ag
13 | 2020/08/01 16:55:19.798 45.439559128 -74.218279859 26.1235 1 10 0.0098 0.0050 0.0156 -0.0017 0.0030 -0.0083
14 | 2020/08/01 16:56:59.757 45.439559237 -74.218279812 26.0935 1 10 0.0091 0.0052 0.0150 0.0043 -0.0025 -0.0072
15 | 2020/08/01 16:57:00.760 45.439559340 -74.218279847 26.0854 1 8 0.0127 0.0052 0.0222 0.0035 0.0020 -0.0140
16 | 2020/08/01 16:57:02.761 45.439559182 -74.218279744 26.1050 1 10 0.0091 0.0051 0.0151 0.0042 -0.0025 -0.0073
17 | 2020/08/01 16:57:04.742 45.439559187 -74.218279884 26.1067 1 10 0.0094 0.0051 0.0156 0.0030 -0.0019 -0.0086
18 | 2020/08/01 16:57:06.763 45.439559173 -74.218279830 26.0945 1 11 0.0092 0.0050 0.0151 0.0032 -0.0025 -0.0081
19 | 2020/08/01 16:57:08.747 45.439559080 -74.218279841 26.1159 1 11 0.0088 0.0048 0.0149 0.0037 -0.0033 -0.0077
20 | 2020/08/01 16:57:10.766 45.439559094 -74.218279795 26.1244 1 11 0.0088 0.0048 0.0150 0.0037 -0.0032 -0.0078
21 | 2020/08/01 16:57:12.773 45.439559111 -74.218279841 26.1146 1 11 0.0089 0.0048 0.0151 0.0037 -0.0032 -0.0079
22 | 2020/08/01 16:57:14.775 45.439559031 -74.218279891 26.1228 1 11 0.0090 0.0048 0.0153 0.0037 -0.0032 -0.0081
23 | 2020/08/01 16:57:16.775 45.439559068 -74.218279882 26.1260 1 11 0.0094 0.0048 0.0160 0.0036 -0.0031 -0.0088
24 | 2020/08/01 16:57:18.777 45.439558933 -74.218279863 26.1464 1 11 0.0087 0.0048 0.0147 0.0037 -0.0033 -0.0075
25 | 2020/08/01 16:57:20.757 45.439558941 -74.218279831 26.1494 1 11 0.0087 0.0048 0.0147 0.0037 -0.0033 -0.0074
26 | 2020/08/01 16:57:22.780 45.439558847 -74.218279818 26.1671 1 11 0.0077 0.0046 0.0129 0.0027 0.0008 -0.0052
27 | 2020/08/01 16:57:24.782 45.439558942 -74.218279838 26.1484 1 11 0.0087 0.0048 0.0147 0.0037 -0.0032 -0.0074

```

- 9.21** Verify that the number of geotags in the events.pos file matches the number of photographs

- 9.22** OPTIONAL STEP: If the number of geotags do not match the number of photographs. Extract photograph exif information with Exiftool to try to figure out which photographs or event tags don't belong (or do not have a match).

Open a command line window.

Navigate to the folder that contains the Exiftool executable.

The following is an example:

```
exiftool -csv D:\MB\2017\geotest\June3\X5S >
```

```
D:\MB\2017\geotest\June3\X5S\exifinfoX5.csv
```

The path is the directory where the jpgs are located.

- 9.23** Delete photographs at the beginning and end of the sequence that were captured on the ground. Delete the corresponding geotags from the events.pos file. Delete the header info and all columns except lat, lon and height. Add a column called "Station" and number consecutively the rows starting from 1. Columns 2-4 should have the following headers: latitude longitude height. Subtract the vertical displacement between the GPS antenna and the camera film plane (~50 cm on the M600P). Save as a .csv file.

	A	B	C	D	E
	Station	latitude	longitude	height	
1	1	45.43955	-74.2183	44.7171	
2	2	45.43955	-74.2183	50.8235	
3	3	45.43955	-74.2183	56.9185	
4	4	45.43955	-74.2183	62.9103	
5	5	45.43955	-74.2183	68.9751	
6	6	45.43955	-74.2183	76.3727	
7	7	45.43955	-74.2183	76.5418	
8	8	45.43945	-74.2182	76.8757	
9	9	45.43943	-74.2181	76.945	
10	10	45.43942	-74.2181	76.8141	
11	11	45.43943	-74.2182	76.6055	

- 9.24** Open GPS-H in a web browser (<https://webapp.geod.nrcan.gc.ca/geod/tools-outils/gpsh.php>) and set up batch processing mode:

Single Calculation Batch Processing

Batch Processing

☐ Convert ☐ Estimate Gravity

Vertical Datum Geoid Reference Frame Epoch (YYYY-MM-DD)

CGVD2013 CGG2013 NAD83(CSRs) 01/01/2010

Select file for batch processing (required)

Choose File No file chosen

Send File

Set the Epoch based on the province the data were collected in. If using Smartnet NA consult <https://support.smartnetna.com/hc/en-us/articles/228080208-SmartNet-Coordinate-Information> for broadcast epoch. Note this may differ from "Provincially adopted Epochs"

Select the .csv file created above and click *Send File*

9.25 GPS will return the processed file with the following columns:

	A	B	C	D	E	F	G	H	I	J
	Station	latitude	longitude	height	N	Ho	Xi	Eta		
1	1	45.43955	-74.2183	44.7171	-30.627	75.344	7.6	-2.2		
2	2	45.43955	-74.2183	50.8235	-30.627	81.45	7.6	-2.2		
3	3	45.43955	-74.2183	56.9185	-30.627	87.545	7.6	-2.2		
4	4	45.43955	-74.2183	62.9103	-30.627	93.537	7.6	-2.2		
5	5	45.43955	-74.2183	68.9751	-30.627	99.602	7.6	-2.2		
6	6	45.43955	-74.2183	76.3727	-30.627	107	7.6	-2.2		
7	7	45.43955	-74.2183	76.5418	-30.627	107.169	7.6	-2.2		
8	8	45.43945	-74.2182	76.8757	-30.626	107.502	7.6	-2.2		
9	9	45.43943	-74.2181	76.945	-30.626	107.571	7.6	-2.2		

The Ho column represents orthometric height

9.26 Create a .csv file with the following columns from the GPSH output: Station, latitude, longitude, Ho. Rename the Ho column to height.

- 9.27 On the TRX webpage (<https://webapp.geod.nrcan.gc.ca/geod/tools-ouils/trx.php>) set up Batch processing mode as:

Batch Processing

☐ Epoch Transformation

Origin

Reference Frame

Epoch (YYYY-MM-DD)

NAD83(CSRs) ▾

01/01/2010

Destination

Reference Frame

Coordinates

Zone ([select zone](#))

NAD83(CSRs) ▾

UTM/MTM/Stereo ▾

UTM18

Select file for batch processing (required)

Choose File

For_TRX.csv

Send File

Make sure to select the correct UTM zone. and Epoch. If using Smartnet NA consult <https://support.smartnetna.com/hc/en-us/articles/228080208-SmartNet-Coordinate-Information> for broadcast epoch. Note this may differ from "Provincially adopted Epochs"

- 9.28 The output from TRX will look like:

TRX_2020-08-11_51683.csv - Excel

	A	B	C	D	E	F	G	H	I	J	K
1	station	utm_z	utm_e	utm_n	height	scale	combined	convergence			
2	1	UTM18	561138.3	5032078	75.344	0.999646	0.999634	-0.557			
3	2	UTM18	561138.4	5032078	81.45	0.999646	0.999633	-0.557			
4	3	UTM18	561138.3	5032078	87.545	0.999646	0.999632	-0.557			
5	4	UTM18	561138.3	5032078	93.537	0.999646	0.999631	-0.557			
6	5	UTM18	561138.4	5032078	99.602	0.999646	0.99963	-0.557			
7	6	UTM18	561138.3	5032078	107	0.999646	0.999629	-0.557			
8	7	UTM18	561139	5032078	107.169	0.999646	0.999629	-0.557			
9	8	UTM18	561148.3	5032066	107.502	0.999646	0.999629	-0.5571			
10	9	UTM18	561149.3	5032065	107.571	0.999646	0.999629	-0.5571			

9.29 Retain the easting, northing and height columns for the generation of the Geotag file for Pix4D (saved as .csv):

	A	B	C	D
1	utm_e	utm_n	height	
2	561138.3	5032078	75.344	
3	561138.4	5032078	81.45	
4	561138.3	5032078	87.545	
5	561138.3	5032078	93.537	
6	561138.4	5032078	99.602	
7	561138.3	5032078	107	
8	561139	5032078	107.169	
9	561148.3	5032066	107.502	
10	561149.3	5032065	107.571	
11	561148.9	5032064	107.44	
12	561148.6	5032064	107.232	
13	561147.4	5032076	106.893	
14	561148.6	5032081	106.787

9.30 Continue with standard Pix4D workflow.