

Oct 22, 2019 Version 1

③ UF H&E Staining V.1

DOI

dx.doi.org/10.17504/protocols.io.8jthunn

Franchesca Farris¹, Marda Jorgensen¹

¹University of Florida

Human BioMolecular Atlas Program (HuBMAP) Method Development Community Tech. support email: Jeff.spraggins@vanderbilt.edu



Franchesca Farris

OPEN ACCESS



DOI: dx.doi.org/10.17504/protocols.io.8jthunn

Protocol Citation: Franchesca Farris, Marda Jorgensen 2019. UF H&E Staining. protocols.io

https://dx.doi.org/10.17504/protocols.io.8jthunn

License: This is an open access protocol distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

We use this protocol in our group and it is working.

Created: October 21, 2019

Last Modified: October 22, 2019

Protocol Integer ID: 29011

Abstract

UF H&E Staining



Materials

MATERIALS

- **⊠** Eosin-Y OPTIK **Catalog** #RS4359-A
- X Hematoxylin OPTIK DK Catalog #RS4576-A
- ⊠ Bluing Reagent OPTIK Catalog #RS-4363-B
- X Aqueous Clarifier Catalog # RS4361-B

1 Place slides into xylene compatible rack. 2 Immerse slide holder in 2 changes of xylene, 5 minutes each. 3 Remove slide holder from xylene and transfer to 2 changes of 100% EtOH for 5 minutes each. 4 Transfer to 95% EtOH for 3 minutes. 5 Transfer to 70% EtOH for 3 minutes. 6 Transfer to 50% EtOH for 3 minutes. 7 Transfer to water for 2 changes, each 2 minutes. 8 Transfer slides to Hematoxylin for 1 minute and 15 seconds. 9 Do a quick dip in water and then transfer slides to water for 30 seconds. 10 Transfer again to water for two changes, each one minute. 11 Transfer to Aqueous Clarifier for 45 seconds. 12 Do a quick dip in water and then transfer to water for 1 minute. 13 Transfer to bluing reagent for 1 minute.

- 14 Place in water for 5 minutes.
- 15 Transfer to 80% EtOH for 1 minute.
- 16 Transfer to Eosin-Y for 1 minute.
- 17 Transfer to 2 changes of 100% EtOH, first change is 2 minutes, second change is 5 minutes.
- 18 Transfer to xylene for two changes, each 5 minutes.
- 19 After the second xylene change, use a xylene compatible mountant.