JUL 14, 2017

OPEN ACCESS

DOI:
dx.doi.org/10.17504/protocols.io.ii2ccge

Protocol Citation: Dr. Steven Wilhelm, Samantha Coy 2017. Using De-MetaST-BLAST. **protocols.io** <https://dx.doi.org/10.17504/protocols.io.ii2ccge>

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

Created: Jun 19, 2017

Last Modified: Mar 24, 2018

PROTOCOL integer ID:
6458

Using De-MetaST-BLAST

Dr. Steven Wilhelm, Samantha Coy

The Aquatic Microbial Ecology Research Group - AMERG (The Buchan, Zinser and Wilhelm labs)

Steven W Wilhelm
 The University of Tennessee, Knoxville

ABSTRACT

Please contact Dr. Steven Wilhelm (wilhelm@utk.edu) or Samantha Coy (srose16@utk.edu) for additional information regarding this protocol.

De-MetaST-BLAST, written in C++, is a script that can validate degenerate primers by performing in silico PCR amplification of the primers against metagenomic and metatranscriptomic databases (e.g. CAMERA; MG-RAST). The output is a list of in-silico PCR amplicons that are then blasted against GenBank to determine the most homologous sequence to the amplicon.

Modified from Gulvik, C. A., Effler, T. C., Wilhelm, S. W., & Buchan, A. (2012). De-MetaST-BLAST: A Tool for the Validation of Degenerate Primer Sets and Data Mining of Publicly Available Metagenomes. *PLoS ONE*, 7(11). doi:10.1371/journal.pone.0050362

BEFORE START INSTRUCTIONS

Requirements:

- Potential degenerate primers
- Linux terminal
- Basic knowledge of navigating directories by command line
- De-MetaST-BLAST program installed

Choosing Degenerate Primers

- 1 Use MEGA to perform an alignment of the gene of interest
- 2 Identify conserved primer regions (18-30nt)
- 3 The predicted amplicon (70-200bp for RT-qPCR) must have enough variability that sequencing these amplicons can distinguish taxonomy

- 4 Check for G4 complexes and other secondary structures that the primers may form
- 5 Check for non-specific amplification and thermal stability for PCR protocols
- 6 Validate primers using De-MetaST-BLAST

Installation of De-MetaST-BLAST

- 7 Install the De-MetaST-BLAST program
<http://sourceforge.net/p/de-metast-blast/>

Execution of De-MetaST-BLAST

- 8 Open the terminal
- 9 `$ cd~/Desktop/Sam/De-MetaST-BLAST/`
(or cd to wherever the program is)
- 10 `$ ./De-MetaST-BLAST CAM_PROJ_X.read.fa`
(execute program, choose database)
- 11 Input filename for primers (press Enter to use Primers.txt)
(Custom file.txt or hit enter)
- 12 <Press Enter>
Opening: Primers.txt
Forward Primer: CARGGNGAYACNCARCC
Reverse Primer: YTTNCCRTCNCCKRYCNGT

13 Searching /home/user/CAMERA_Databases/CAM_PROJ_X.read.fa

14 Remote BLASTx running...
BLASTx finished
\$